

# DS-2CE16D0T-ITFS

Hikvision DS-2CE16D0T-ITFS 2 mp meqapiksel TVI səsli video kamera; Piksel 1920×1080; IR işıqlandırma - 30 m; F2,8 mm; Bucaq-106.4°; Audio (Mikrofon)

Model	DS-2CE16D0T-ITFS
Brend	Hikvision
Növ	Analoq
Meqapixel	2 MP
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8
İşıqlandırma	IR
İşıqlandırma məsafəsi	30 m
Qoruma	IP67
Material	Metal



## Specification

• Specification	
Camera	
Image Sensor	2.0 megapixel progressive scanCMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.01 Lux @ (F2.0, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s
Day & Night	ICR
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 180°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm, 3.6 mm, 6 mm fixedlens
Focal Length & FOV	2.8 mm, horizontal FOV: 106.4°, vertical FOV: 57.9°, diagonal FOV: 124.6° 3.6 mm, horizontal FOV: 79.6°, vertical FOV: 43.5°, diagonal FOV: 93.7° 6 mm, horizontal FOV: 51.9°, vertical FOV: 30°, diagonal FOV: 58.8
Lens Mount	M12
Image	
Image Settings	Brightness, Sharpness, Mirror, Smart IR

<b>Frame Rate</b>	<b>TVI: 1080P@30fps, 1080P@25fps AHD: 1080P@30fps, 1080P@25fps CVI: 1080P@30fps, 1080P@25fps CVBS: PAL/NTSC</b>
<b>Day/Night Mode</b>	<b>Auto/Color/BW (Black and White)</b>
<b>Wide Dynamic Range (WDR)</b>	<b>Digital WDR</b>
<b>Image Enhancement</b>	<b>Yes</b>
<b>Image Enhancement</b>	<b>Yes</b>
<b>White Balance</b>	<b>Auto/Manual</b>
<b>AGC</b>	<b>Support</b>
<b>Interface</b>	
<b>Video Output</b>	<b>Switchable TVI/AHD/CVI/CVBS</b>
<b>General</b>	
<b>Material</b>	<b>Metal</b>
<b>Dimension</b>	<b>58 mm × 61mm × 158.6 mm (2.28" × 2.40" × 6.42")</b>
<b>Weight</b>	<b>Approx. 292 g(0.64 lb.)</b>
<b>Operating Condition</b>	<b>-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)</b>
<b>Communication</b>	<b>HIKVISION-C</b>
<b>Language</b>	<b>English</b>
<b>Power Supply</b>	<b>12 VDC ± 25%</b>
<b>Consumption</b>	<b>Max. 3.7 W</b>
<b>IR Range</b>	<b>Up to 30 m</b>
<b>Approval</b>	
<b>Protection</b>	<b>IP67</b>