

# DS-2CE16D0T-LPFS

Hikvision DS-2CE16D0T-LPFS 2 mp meqapiksel TVI səsli video kamera; Piksel 1920×1080; IR işıqlandırma - 25 m; F2,8 mm; Bucaq-101°; Audio (Mikrofon)

Model	DS-2CE16D0T-LPFS
Brend	Hikvision
Növ	Analoq
Meqapixel	2 MP
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8
İşıqlandırma	İR
İşıqlandırma məsafəsi	25 m
Qoruma	IP67
Material	Plastik



## Specification

• Specification	
Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.01 Lux @ (F1.6, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 to 1/50, 000 s; NTSC: 1/30 s to 1/50, 000s
Day & Night	ICR
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 180°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm, 3.6 mm fixedfocal lens
Focal Length & FOV	2.8 mm, horizontal FOV: 101°, vertical FOV: 56°, diagonal FOV: 118° 3.6 mm, horizontal FOV: 78°, vertical FOV: 42°, diagonal FOV: 92°
Lens Mount	M12
Illuminator	
Supplement Light Type	White Light, IR
Supplement Light Range	IR : Up to 25 m White Light : Up to 20 m

<b>Image</b>	
<b>Image Settings</b>	Brightness, Sharpness, Smart IR
<b>Frame Rate</b>	TVI: 1080P @ 30 fps, 1080P @ 25 fps AHD: 1080P @ 30 fps, 1080P @ 25 fps CVI: 1080P @ 30 fps, 1080P @ 25 fps CVBS: PAL/NTSC
<b>Day/Night Mode</b>	Auto/Color/BW (Blackand White)
<b>Wide Dynamic Range (WDR)</b>	Digital WDR
<b>Image Enhancement</b>	DWDR/BLC/HLC/Global
<b>White Balance</b>	Auto/Manual
<b>AGC</b>	Yes
<b>Interface</b>	
<b>Video Output</b>	Switchable TVI/AHD/CVI/CVBS
<b>Built-in Microphone</b>	Yes
<b>General</b>	
<b>Material</b>	Plastic
<b>Dimension</b>	138.8 mm × 60.9 mm × 57.9mm (5.47" × 2.4 "× 2.3")
<b>Weight</b>	Approx. 155 g(0.34 lb.)
<b>Operating Condition</b>	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
<b>Communication</b>	HIKVISION-C
<b>Language</b>	English
<b>Power Supply</b>	12 VDC ± 25% *You are recommended to use one power adapter to supply the power for one camera.
<b>Consumption</b>	Max. 3.3 W
<b>Approval</b>	
<b>Protection</b>	IP67