

HIKVISION**DS-2CE16D8T-IT3ZF**

Kod: 00-00000400 · Kamera



Hikvision DS-2CE16D8T-IT3ZF 2MP Turbo HD Kamera 2.7-13.5mm motorlu lens ilə çevik baxış sahəsi təmin edir. IR gecə görmə ilə zəif işıq şəraitində belə yüksək keyfiyyətli görüntü təmin edir və ev və iş yerləri üçün etibarlı təhlükəsizlik həlli təqdim edir.

Qiymət, stok və sifariş üçün: [Məhsul səhifəsinə keçin →](https://eurotechnology.az/product/hikvision/ds-2ce16d8t-it3zf)
<https://eurotechnology.az/product/hikvision/ds-2ce16d8t-it3zf>

Texniki göstəricilər**Analoq**

Növ

**2 MP**

Məqapixel

**Motorized**

Obyektiv

**2.7 - 13.5mm**

Fokus

**İR**

İşıqlandırma

**80 m**

İşıqlandırma məsafəsi

**IP67**

Qoruma

**Metal**

Material

**Outdoor**

İş mühiti

Ətraflı məlumat

Category	Specification
Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	Color: 0.003 Lux @(F1.87, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 sNTSC: 1/30 s to 1/50,000 s
Day & Night	ICR
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.7 mm to 13.5 mm motorized, auto focus
Focal Length & FOV	103° to 32.1°
Lens Mount	M12
Image	
Image Parameters Switch	STD/HIGH-SAT
Image Settings	Brightness, Sharpness, Mirror, Smart IR
Frame Rate	PAL: 1080p @ 25 fpsNTSC: 1080p @ 30 fps
Day/Night Mode	Auto / Color / BW (Black and White)
Wide Dynamic Range (WDR)	≥ 130 dB
Image Enhancement	BLC, HLC
White Balance	ATW / Manual
AGC	Support
Interface	
Video Output	Switchable TVI / AHD / CVI / CVBS
General	
Material	Metal

Category	Specification
Dimension	85 mm × 92 mm × 269.6 mm (3.3" × 3.6" × 10.6")
Weight	Approx. 910 g (2.01 lb)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), Humidity ≤90% (no condensation)
Communication	HIKVISION-C
Language	English
Power Supply	12 VDC ± 25%
Consumption	Max. 7.5 W
IR Range	Up to 80 m
Approval	
Protection	IP67

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az