

DS-2CE16H0T-ITF

DS-2CE16H0T-ITF 2,8MM 5MP HD TVI KAMERA HIKVISION

Model	DS-2CE16H0T-ITF
Brend	Hikvision
Qoruma	IP67
Material	Metal
Növ	Analoq
Meqapixel	5 MP
Obyektiv	Sabit
Fokus	2.8mm
İşıqlandırma	İR
İşıqlandırma məsafəsi	20 m
İş mühiti	Outdoor



Specification

Camera	
Image Sensor	5 MP CMOS imagesensor
Resolution	2560 (H) × 1944 (V)
Min. Illumination	Color: 0.01Lux @ (F1.2,AGC ON), 0 Lux withIR
Shutter Time	PAL: 1/25 s to 1/50,000 s NTSC: 1/30s to 1/50, 000 s
Lens	2.8 mm, 3.6 mm,6 mm fixed focal lens
Horizontal Fieldof View	85.5° (2.8 mm), 80.1° (3.6 mm), 57.1° (6 mm)
Lens Mount	M12
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°;Tilt: 0° to 180°; Rotate:0° to 360°
Synchronization	Internal synchronization
Frame Rate	PAL: 5 MP@20fps, 4 MP@25fps, 1080p@25fps NTSC: 5 MP@20fps, 4 MP@30fps, 1080p@30fps
Menu	
AGC	Support
D/N Mode	Auto/Color/BW (Blackand White)
White Balance	ATW/MWB
BLC	Support
DWDR (Digital Wide DynamicRange)	Support

Language	English
Functions	Brightness, Sharpness, DNR , Mirror, Smart IR
<i>Interface</i>	
Video Output	1 HD analog output
Switch Button	TVI/AHD/CVI/CVBS
<i>General</i>	
Operating Conditions	-40 °C to 60 °C (-40°F to 140 °F), humidity: 90% or less(non-condensation)
Power Supply	12 VDC ±25%
Power Consumption	Max. 4.3 W
Protection Level	IP67
Material	Metal
IR Range	Up to 20 m
Communication	Up the coax, Protocol: HIKVISION-C (TVI output)
Dimensions	58 mm × 61 mm × 163 mm (2.28" × 2.40" × 6.42")
Weight	Approx. 350 g(0.77 lb.)