

DS-2CE17D0T-IT3

Hikvision DS-2CE17D0T-IT3 2MP HD TVI Bullet Kamera 3.6mm lens ilə geniş baxış sahəsi təqdim edir. 40 metr IR gecə görmə funksiyası sayəsində zəif işıqda belə dəqiq görüntü təmin edir. Eviniz və iş yeriniz üçün etibarlı və effektiv təhlükəsizlik həlli.



Specifications

Model	DS-2CE17D0T-IT3
Brand	Hikvision
Növ	Analoq
Meqapixel	2 MP
???qland?rma m?saf?si	40 m
???qland?rma	IR
Obyektiv	Sabit
Fokus	3.6mm
Qoruma	IP67
Material	Plastik
?? mühiti	Outdoor

KEY FEATURES

Category	Specification
Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.01 Lux @(F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 sNTSC: 1/30 s to 1/50,000 s
Day & Night	ICR
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 180°, Rotation: 0° to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed lens
Focal Length & FOV	2.8 mm: H 106.4°, V 57.9°, D 124.6°3.6 mm: H 79.6°, V 43.5°, D 93.7°6 mm: H 51.9°, V 30°, D 58.8°8 mm: H 39.9°, V 21.9°, D 46.5°12 mm: H 24.6°, V 13.9°, D 28.1°
Lens Mount	M12
Image	
Image Parameters	STD/HIGH-SAT
Switch	
Image Settings	Brightness, Sharpness, Smart IR
Frame Rate	TVI: 1080P @ 30 fps, 1080P @ 25 fps
Day/Night Mode	Auto / Color / BW (Black and White)
Wide Dynamic Range (WDR)	Digital WDR
Image Enhancement	DWDR / BLC / HLC / Global
Noise Reduction	Yes
White Balance	Auto / Manual
AGC	Yes
Interface	
Video Output	1 HD analog output
General	
Material	Front Cover: MetalMain Body: Plastic
Dimension	78.9 mm × 75.4 mm × 216.6 mm (3.10" × 2.97" × 8.53")
Weight	Approx. 315 g (0.69 lb)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity ≤90% (non-condensing)
Communication	HIKVISION-C
Language	English
Power Supply	12 VDC ± 25%
Consumption	Max. 3.9 W
IR Range	Up to 40 m
Approval	
Protection	IP67