

# DS-2CE17H0T-IT3F

## HIKVISION DS-2CE17H0T-IT3F TURBO HD KAMERA

Model	DS-2CE17H0T-IT3F
Brend	Hikvision
Növ	Analoq
Meqapixel	5 MP
İşıqlandırma məsafəsi	40 m
Obyektiv	Sabit
Fokus	2.8
İşıqlandırma	İR
Qoruma	IP67
Material	Metal



## Specification

Camera	
Image Sensor	5 MP CMOS
Signal System	PAL/NTSC
Frame Rate	TVI: 5M@20fps, 4M@30fps, 4M@25fps, 1080p@30fps, 1080p@25fps AHD: 5M@20fps, 4M@30fps, 4M@25fps CVI: 4M@30fps, 4M@25fps CVBS: PAL/NTSC
Resolution	2560 (H) × 1944 (V)
Min. illumination	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s
Lens	2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed lens
Horizontal Fieldof View	2.8 mm, horizontal FOV: 85°, vertical FOV: 63°, diagonal FOV:110° 3.6 mm, horizontal FOV: 80°, vertical FOV: 63°, diagonal FOV:105° 6 mm, horizontal FOV:57°, vertical FOV: 43°, diagonal FOV:72° 8 mm, horizontal FOV: 41°, vertical FOV: 31°, diagonal FOV:52° 12 mm, horizontal FOV: 26°, vertical FOV: 19°, diagonal FOV:32°
Lens Mount	M12
Day & Night	ICR
WDR (Wide Dynamic Range)	Digital WDR
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 180°, Rotation 0 to 360°
Menu	
Image Mode	STD/HIGH-SAT
AGC	Support
Day/Night Mode	Auto/Color/BW (Black and White)
White Balance	Auto/Manual
AE (Auto Exposure) Mode	DWDR/BLC/HLC/Global
Language	English
Functions	Brightness, Sharpness, Mirror, Smart IR
2D DNR	Yes

<b>Interface</b>	
<b>Video Output</b>	TVI/AHD/CVI/CVBS
<b>General</b>	
<b>Operating Condition</b>	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
<b>Power Supply</b>	12 VDC ± 25%
<b>Power Consumption</b>	Max. 4.3 W
<b>Protection Level</b>	IP67
<b>Material</b>	Front Cover: Metal Main Body: Plastic
<b>IR Range</b>	Up to 40 m
<b>Communication</b>	HIKVISION-C
<b>Dimensions</b>	78.9 mm × 75.4 mm × 216.6mm (3.10" × 2.97" × 8.53")
<b>Weight</b>	Approx. 330 g (0.73lb.)