

DS-2CE18D0T-LFS

DS-2CE18D0T-LFS 2.8mm 2mp IR 60m LED 60m built-in mic Bullet Camera Hikvision

Model	DS-2CE18D0T-LFS
Brend	Hikvision
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma məsafəsi	60 m
Obyektiv	Sabit
Fokus	2.8
İşıqlandırma	İR
Qoruma	IP67
Material	Metal



Specification

Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080(V)
Min. Illumination	0.01 Lux @ (F2.0, AGCON), 0 Lux with white light
Shutter Time	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30s to 1/50,000 s
Day / Night	ICR
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 180°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	Fixed focallens, 2.8 mm, 3.6 mm and 6 mm optional
Focal Length / FOV	2.8 mm, horizontal FOV: 101°, vertical FOV: 56°, diagonal FOV: 118° 3.6 mm, horizontal FOV: 78°, vertical FOV: 42°, diagonal FOV: 92° 6 mm, horizontal FOV: 49.2°, vertical FOV: 28.3°, diagonal FOV: 56.1°
Lens Mount	M12
Illuminator	
Supplement Light Type	White Light, IR
Supplement Light Range	IR : Up to 60 m White Light: Up to 60 m
Image	
Image Settings	Anti-Banding, Brightness, Sharpness, Smart IR
Frame Rate	TVI: 1080P @ 30 fps, 1080P @ 25 fps AHD: 1080P @ 30 fps, 1080P @ 25 fps CVI: 1080P @ 30 fps, 1080P @ 25 fps CVBS: PAL/NTSC
Day/Night Mode	Auto/Color/BW (Black and White)

Wide Dynamic Range(WDR)	Digital WDR
Image Enhancement	DWDR/BLC/HLC/Global
White Balance	Auto/Manual
AGC	Yes
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS
General	
Power	12 VDC \pm 25%, max.9.8 W,*Youare recommended to use onepower adapter to supply the power for one camera.
Material	Front cover: Metal Main body:Plastic
Dimension	192.6 mm \times 178.3 mm \times 71 mm (7.58" \times 7.02" \times 2.8")
Weight	Approx. 738 g (1.63 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less(non-condensation)
Communication	HIKVISION-C
Language	English
Approval	
Protection	IP67