

# DS-2CE18D0T-LFS

DS-2CE18D0T-LFS 2.8mm 2mp IR 60m LED 60m built-in mic Bullet Camera Hikvision



## Specifications

Model	DS-2CE18D0T-LFS
Brand	Hikvision
?? mühiti	Outdoor
Növ	Analoq
Meqapixel	2 MP
Mikrofon	Mic
???qland?rma m?saf?si	60 m
Obyektiv	Sabit
Fokus	2.8mm
???qland?rma	İR
Qoruma	IP67
Material	Metal

## KEY FEATURES

### Camera

<b>Image Sensor</b>	2 MP CMOS
<b>Max. Resolution</b>	1920 (H) × 1080(V)
<b>Min. Illumination</b>	0.01 Lux @ (F2.0, AGCON), 0 Lux with white light
<b>Shutter Time</b>	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30s to 1/50,000 s
<b>Day &amp; Night</b>	ICR
<b>Angle Adjustment</b>	Pan: 0 to 360°, Tilt:0 to 180°, Rotation: 0 to 360°
<b>Signal System</b>	PAL/NTSC

### Lens

<b>Lens Type</b>	Fixed focallens, 2.8 mm, 3.6 mm and 6 mm optional
	2.8 mm, horizontal FOV: 101°, vertical FOV: 56°, diagonal FOV: 118°
<b>Focal Length &amp; FOV</b>	3.6 mm, horizontal FOV: 78°, vertical FOV: 42°, diagonal FOV: 92°
	6 mm, horizontal FOV:49.2°, vertical FOV:28.3°, diagonal FOV: 56.1°

<b>Lens Mount</b>	M12
-------------------	-----

### Illuminator

<b>Supplement LightType</b>	White Light,IR
<b>Supplement LightRange</b>	IR : Up to 60 m
	White Light: Up to 60 m

### Image

<b>Image Settings</b>	Anti-Banding, Brightness, Sharpness, Smart IR
	TVI: 1080P @ 30 fps, 1080P @ 25 fps AHD: 1080P@ 30 fps, 1080P@ 25 fps CVI: 1080P@ 30 fps, 1080P @ 25 fps
	CVBS: PAL/NTSC

### Frame Rate

<b>Day/Night Mode</b>	Auto/Color/BW (Black and White)
-----------------------	---------------------------------

**Wide Dynamic Range(WDR)** Digital WDR

<b>Image Enhancement</b>	DWDR/BLC/HLC/Global
--------------------------	---------------------

<b>White Balance</b>	Auto/Manual
----------------------	-------------

<b>AGC</b>	Yes
------------	-----

### Interface

<b>Video Output</b>	Switchable TVI/AHD/CVI/CVBS
---------------------	-----------------------------

### General

<b>Power</b>	12 VDC ± 25%, max.9.8 W,*Youare recommended
	to use onepower adapter to supply
	the power for one camera.

---

<b>Material</b>	<b>Front cover: Metal</b> <b>Main body:Plastic</b>
<b>Dimension</b>	<b>192.6 mm × 178.3 mm ×71 mm (7.58" × 7.02" × 2.8")</b>
<b>Weight</b>	<b>Approx. 738 g (1.63 lb.)</b>
<b>Operating Condition</b>	<b>-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less(non-condensation)</b>
<b>Communication</b>	<b>HIKVISION-C</b>
<b>Language</b>	<b>English</b>
<b>Approval</b>	
<b>Protection</b>	<b>IP67</b>