

# DS-2CE18D0T-LFS

DS-2CE18D0T-LFS 2.8mm 2mp IR 60m LED 60m built-in mic Bullet Camera Hikvision

Model	DS-2CE18D0T-LFS
Brend	Hikvision
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma məsafəsi	60 m
Obyektiv	Sabit
Fokus	2.8
İşıqlandırma	İR
Qoruma	IP67
Material	Metal



## Specification

Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080(V)
Min. Illumination	0.01 Lux @ (F2.0, AGCON), 0 Lux with white light
Shutter Time	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30s to 1/50,000 s
Day & Night	ICR
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 180°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	Fixed focallens, 2.8 mm, 3.6 mm and 6 mm optional
Focal Length & FOV	2.8 mm, horizontal FOV: 101°, vertical FOV: 56°, diagonal FOV: 118° 3.6 mm, horizontal FOV: 78°, vertical FOV: 42°, diagonal FOV: 92° 6 mm, horizontal FOV: 49.2°, vertical FOV: 28.3°, diagonal FOV: 56.1°
Lens Mount	M12
Illuminator	
Supplement LightType	White Light, IR
Supplement LightRange	IR : Up to 60 m White Light: Up to 60 m
Image	
Image Settings	Anti-Banding, Brightness, Sharpness, Smart IR

<b>Frame Rate</b>	TVI: 1080P @ 30 fps, 1080P @ 25 fps AHD: 1080P@ 30 fps, 1080P@ 25 fps CVI: 1080P@ 30 fps, 1080P @ 25 fps CVBS: PAL/NTSC
<b>Day/Night Mode</b>	Auto/Color/BW (Black and White)
<b>Wide Dynamic Range(WDR)</b>	Digital WDR
<b>Image Enhancement</b>	DWDR/BLC/HLC/Global
<b>White Balance</b>	Auto/Manual
<b>AGC</b>	Yes
<b>Interface</b>	
<b>Video Output</b>	Switchable TVI/AHD/CVI/CVBS
<b>General</b>	
<b>Power</b>	12 VDC $\pm$ 25%, max.9.8 W,*Youare recommended to use onepower adapter to supply the power for one camera.
<b>Material</b>	Front cover: Metal Main body:Plastic
<b>Dimension</b>	192.6 mm $\times$ 178.3 mm $\times$ 71 mm (7.58" $\times$ 7.02" $\times$ 2.8")
<b>Weight</b>	Approx. 738 g (1.63 lb.)
<b>Operating Condition</b>	-40 $^{\circ}$ C to 60 $^{\circ}$ C (-40 $^{\circ}$ F to 140 $^{\circ}$ F), humidity: 90% or less(non-condensation)
<b>Communication</b>	HIKVISION-C
<b>Language</b>	English
<b>Approval</b>	
<b>Protection</b>	IP67