

DS-2CE19D3T-IT3ZF

Hikvision DS-2CE19D3T-IT3ZF 2 MP varifokal TVI video kamera; Piksel 1920×1080; IR işıqlandırma - 70 m; F2.7-13.5 mm; Bucaq: 102° - 31°;

Model	DS-2CE19D3T-IT3ZF
Brend	Hikvision
Qoruma	IP67
Növ	Analoq
Meqapixel	2 MP
Obyektiv	Motorized
Fokus	2.7 - 13.5mm
İşıqlandırma məsafəsi	70 m
İşıqlandırma	İR
Material	Metal
İş mühiti	Outdoor



Specification

Camera

Matrix	2 MP Progressive Scan CMOS
Number of effective pixels	1920×1080
Sensitivity	0.005 Lux @ (F1.2, AGC on), 0 Lux with IR
Electronic shutter speed	PAL: 1/25 – 1/50,000 s NTSC: 1/30 – 1/50,000 s
Lens	From 2.7 to 13.5 mm
Lens mount	F14
Horizontal viewing angle	102 to 31°
Adjusting the viewing angle	Rotation: 0° - 360°; Tilt: 0° - 180°; Rotation: 0° - 360°
Synchronization	Internal

OSD menu

A.G.C.	High/Medium/Low
Day/night switching	Auto/Color/B&W
Picture Mode	STD/HIGH-SAT
WDR	There is
BLC	There is
Language	English
Peculiarities	3D DNR, Brightness, Sharpness, Mirroring, Smart IR

Interfaces

Video output	1 analog HD video output
Switch button	TVI/AHD/CVI/CVBS

Basics

Nutrition	DC 12V \pm 25%
Connection	Coaxial cable, HIKVISION-C protocol (TVI output)
Power consumption	7.7 W max
Working conditions	-40 °C...+60 °C, humidity 90% or less (non-condensing)
Protection	IP67
IR illumination range	Up to 70 m
Housing material	Metal
Dimensions	84.5 × 92 × 255.1 mm
Weight	Approximately 648 g