

DS-2CE19H0T-AIT3ZF

DS-2CE19H0T-AIT3ZF 2.7-13.5mm 5mp IR 40m VF Bullet HD TVI KAMERA HIKVISION



Specifications

Model	DS-2CE19H0T-AIT3ZF
Brand	Hikvision
Qoruma	IP67
Növ	Analoq
Meqapixel	5 MP
Obyektiv	Motorized
Fokus	2.7 - 13.5mm
???qland?rma	İR
???qland?rma m?saf?si	40 m
Material	Plastik
?? mühiti	Outdoor

KEY FEATURES

Camera	
Image Sensor	5 MP CMOS
Signal System	PAL/NTSC
Resolution	2560 (H) × 1944(V) TVI: 5 M @ 20 fps, 4 M @ 30 fps, 4 M @ 25 fps, 1080p @ 30 fps , 1080p @ 25 fps
Frame Rate	AHD: 5 M @ 20 fps, 4 M @ 30 fps, 4 M @ 25fps CVI: 4 M @ 30 fps, 4 M @ 25 fps CVBS: PAL/NTSC
Min. Illumination	0.01 Lux @ (F1.6, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25s to 1/50,000 s; NTSC: 1/30s to 1/50,000 s
Lens	2.7 mm to 13.5 mm motorized varifocal lens
Field of View	horizontal FOV: 95° to 26°, vertical FOV: 72° to 20°, diagonal FOV: 126° to 33°
Lens Mount	Φ14
Day / Night	IR Cut Filter
WDR (Wide Dynamic Range)	Digital WDR
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 90°, Rotation: 0° to 360°
Image	
Day/Night Mode	Auto/Color/BW (Black and White)
Image Mode	STD/HIGH-SAT
AGC	Yes
White Balance	Auto/Manual
AE (Auto Exposure) Mode	DWDR, BLC, HLC, Global
Noise Reduction	2D DNR
Language	English
Function	Brightness, Smart IR, Sharpness
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS
General	
IR Range	Up to 40 m
Operating Conditions	-40°C to 60°C (-40°F to 140°F), Humidity: 90% or less (non-condensing)
Power Supply	12 VDC ± 15%, 24 VAC ± 15%
Consumption	Max 8.8 W
Protection Level	IP67
Material	Front cover: Metal, Mainbody: Plastic
Communication	HIKVISION-C
Dimension	84.5 mm × 92 mm × 255.1 mm (3.33" × 3.62" × 10.04")
Weight	Approx. 682 g (1.50 lb.)