

## DS-2CE56D0T-IRM

Hikvision DS-2CE56D0T-IRM 2 mp meqapiksel TVI video kamera; Piksel 1920×1080; IR işıqlandırma - 20 m; F2,8 mm; Bucaq-101°;



### Specifications

Model	DS-2CE56D0T-IRM
Brand	Hikvision
Qoruma	IP67
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma məsafəsi	20 m
Obyektiv	Sabit
Fokus	2.8mm
İşıqlandırma	İR
Material	Metal
İstifadə mühiti	Indoor

## KEY FEATURES

## Camera

<b>Image Sensor</b>	2 MP CMOS
<b>Max. Resolution</b>	1920 (H) × 1080 (V)
<b>Min. Illumination</b>	0.01Lux @ (F2.0, AGC ON), 0 Lux with IR
<b>Shutter Time</b>	PAL: 1/25 s to 1/50,000 s NTSC: 1/30s to 1/50,000 s
<b>Day &amp; Night</b>	ICR
<b>Angle Adjustment</b>	Pan: 0 to 360°, Tilt: 0 to 75°, Rotation: 0 to 360°
<b>Signal System</b>	PAL/NTSC
<b>Lens</b>	
<b>Lens Type</b>	2.8 mm, 3.6 mm, 6 mm fixedlens
	2.8 mm, horizontal FOV: 101°, vertical FOV: 60°, diagonal FOV: 122°
<b>Focal Length &amp; FOV</b>	3.6 mm, horizontal FOV: 79.6°, vertical FOV: 43.5°, diagonal FOV: 93.7° 6 mm, horizontal FOV: 51.9°, vertical FOV: 30°, diagonal FOV: 58.8°
<b>Lens Mount</b>	M12
<b>Image</b>	
<b>Image Parameters Switch</b>	STD/HIGH-SAT
<b>Image Settings</b>	Brightness, Sharpness, SmartIR
<b>Frame Rate</b>	TVI: 1080P@30fps, 1080P@25fps
<b>Day/Night Mode</b>	Auto/Color/BW (Black and White)
<b>Wide Dynamic Range (WDR)</b>	Digital WDR
<b>Image Enhancement</b>	BLC, HLC
<b>White Balance</b>	Auto/Manual
<b>AGC</b>	Yes
<b>Interface</b>	
<b>Video Output</b>	1 HD analog output
<b>General</b>	
<b>Material</b>	Metal
<b>Dimension</b>	89.47 mm × 67.6mm (3.52" × 2.70")
<b>Weight</b>	Approx. 250 g (0.55lb.)
<b>Operating Condition</b>	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
<b>Communication</b>	HIKVISION-C
<b>Language</b>	English
<b>Power Supply</b>	12 VDC ± 25%
<b>Consumption</b>	Max. 3 W
<b>IR Range</b>	Up to 25 m
<b>Approval</b>	
<b>Protection</b>	IP67