

# DS-2CE56D0T-IRP

Hikvision DS-2CE56D0T-IRP 2 mp TVI video kamera; Piksel 1920×1080; IR işıqlandırma - 20 m; F2,8 mm; Bucaq-101°;



Model	DS-2CE56D0T-IRP
Brend	Hikvision
Material	Plastik
İş mühiti	Indoor
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma məsafəsi	20 m
Obyektiv	Sabit
Fokus	2.8mm
İşıqlandırma	İR

## Specification

Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.01Lux @ (F2.0, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s NTSC: 1/30s to 1/50,000 s
Day / Night	ICR
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 75°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm, 3.6 mm, 6 mm fixedlens
Focal Length / FOV	2.8 mm, horizontal FOV: 101°, vertical FOV: 60°, diagonal FOV: 122° 3.6 mm, horizontal FOV: 79.6°, vertical FOV: 43.5°, diagonal FOV: 93.7° 6 mm, horizontal FOV: 51.9°, vertical FOV: 30°, diagonal FOV: 58.8°
Lens Mount	M12
Image	
Image Parameters Switch	STD/HIGH-SAT
Image Settings	Brightness, Sharpness, SmartIR
Frame Rate	TVI: 1080P@30fps, 1080P@25fps
Day/Night Mode	Auto/Color/BW (Black and White)
Wide Dynamic Range (WDR)	Digital WDR
Image Enhancement	BLC, HLC
White Balance	Auto/Manual
AGC	Yes
Interface	
Video Output	1 HD analog output
General	

<b>Material</b>	Plastic
<b>Dimension</b>	Φ 89.9 mm × 70.1mm (Φ 3.54" × 2.76")
<b>Weight</b>	Approx. 130 g (0.29lb.)
<b>Operating Condition</b>	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
<b>Communication</b>	HIKVISION-C
<b>Language</b>	English
<b>Power Supply</b>	12 VDC ± 25%
<b>Consumption</b>	Max. 2.2 W
<b>IR Range</b>	Up to 20 m