

DS-2CE56D0T-IT3E

DS-2CE56D0T-IT3E



Specifications

Model	DS-2CE56D0T-IT3E
Brand	Hikvision
Qoruma	IP67
Növ	Analoq
Meqapixel	2 MP
??qland?rma m?saf?si	30 m
Obyektiv	Sabit
Fokus	2.8mm
??qland?rma	IR
Material	Plastik
?? mühiti	Indoor

KEY FEATURES

Camera	
Image Sensor	2.0 megapixel progressive scanCMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.01 Lux@(F2.0, AGC ON), 0 Lux withIR
Shutter Time	PAL: 1/25s to 1/50,000 s;NTSC: 1/30s to 1/50,000 s
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 75°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed lens
	2.8 mm, horizontal FOV:103.55°
	3.6 mm, horizontal FOV: 82.63° 6 mm, horizontal FOV: 54.38°
Focal Length& FOV	8 mm, horizontal FOV:37.96
	12 mm, horizontal FOV:24.36
Lens Mount	M12
Illuminator	
Supplement LightRange	Up to 30 m
Image	
Image Settings	Brightness, Mirror, Sharpness, AGC
Frame Rate	PAL: 1080P@25fps
	NTSC: 1080P@30fps
Day/Night Mode	Auto/Color/BW (Blackand White)
Wide Dynamic Range (WDR)	Digital WDR
Image Enhancement	DWDR, BLC
Noise Reduction	2D DNR
Supplement Detection(PIR)	
PIR Range	Up to 40 m
Interface	
Video Output	1 HD analog output
General	
Power	12 VDC ±30%/PoC.af, max. 4W
Material	Plastic
Dimension	110 mm × 93.2 mm (4.33" × 3.67")
Weight	Approx. 350 g(0.77 lb.)
Operating Condition	-40 °C to 60 °C(-40 °F to 140 °F), humidity 90% or less(non-condensing)
Communication	HIKVISION-C
Language	English
Approval	
Protection	IP67