

# DS-2CE56D0T-IT3E

DS-2CE56D0T-IT3E



Model	DS-2CE56D0T-IT3E
Brend	Hikvision
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma məsafəsi	30 m
Obyektiv	Sabit
Fokus	2.8
İşıqlandırma	İR
Qoruma	IP67
Material	Plastik

## Specification

Camera	
Image Sensor	2.0 megapixel progressive scanCMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.01 Lux@(F2.0, AGC ON), 0 Lux withIR
Shutter Time	PAL: 1/25s to 1/50,000 s;NTSC: 1/30s to 1/50,000 s
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 75°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed lens
Focal Length & FOV	2.8 mm, horizontal FOV:103.55° 3.6 mm, horizontal FOV: 82.63° 6 mm, horizontal FOV: 54.38° 8 mm, horizontal FOV:37.96 12 mm, horizontal FOV:24.36
Lens Mount	M12
Illuminator	
Supplement LightRange	Up to 30 m
Image	
Image Settings	Brightness,Mirror,Sharpness,AGC

<b>Frame Rate</b>	<b>PAL: 1080P@25fps</b> <b>NTSC: 1080P@30fps</b>
<b>Day/Night Mode</b>	<b>Auto/Color/BW (Blackand White)</b>
<b>Wide Dynamic Range (WDR)</b>	<b>Digital WDR</b>
<b>Image Enhancement</b>	<b>DWDR,BLC</b>
<b>Noise Reduction</b>	<b>2D DNR</b>
<b>Supplement Detection(PIR)</b>	
<b>PIR Range</b>	<b>Up to 40 m</b>
<b>Interface</b>	
<b>Video Output</b>	<b>1 HD analog output</b>
<b>General</b>	
<b>Power</b>	<b>12 VDC ±30%/PoC.af, max. 4W</b>
<b>Material</b>	<b>Plastic</b>
<b>Dimension</b>	<b>110 mm × 93.2 mm (4.33" × 3.67")</b>
<b>Weight</b>	<b>Approx. 350 g(0.77 lb.)</b>
<b>Operating Condition</b>	<b>-40 °C to 60 °C(-40 °F to 140 °F), humidity 90% or less(non-condensing)</b>
<b>Communication</b>	<b>HIKVISION-C</b>
<b>Language</b>	<b>English</b>
<b>Approval</b>	
<b>Protection</b>	<b>IP67</b>