

DS-2CE56D0T-IT3E

DS-2CE56D0T-IT3E

Model	DS-2CE56D0T-IT3E
Brend	Hikvision
Qoruma	IP67
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma məsafəsi	30 m
Obyektiv	Sabit
Fokus	2.8mm
İşıqlandırma	İR
Material	Plastik
İş mühiti	Indoor



Specification

Camera	
Image Sensor	2.0 megapixel progressive scan CMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.01 Lux@(F2.0, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25s to 1/50,000 s; NTSC: 1/30s to 1/50,000 s
Day / Night	IR Cut Filter
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 75°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed lens
Focal Length / FOV	2.8 mm, horizontal FOV: 103.55° 3.6 mm, horizontal FOV: 82.63° 6 mm, horizontal FOV: 54.38° 8 mm, horizontal FOV: 37.96° 12 mm, horizontal FOV: 24.36°
Lens Mount	M12
Illuminator	
Supplement Light Range	Up to 30 m
Image	
Image Settings	Brightness, Mirror, Sharpness, AGC
Frame Rate	PAL: 1080P@25fps NTSC: 1080P@30fps
Day/Night Mode	Auto/Color/BW (Black and White)
Wide Dynamic Range (WDR)	Digital WDR
Image Enhancement	DWDR, BLC
Noise Reduction	2D DNR

Supplement Detection(PIR)	
PIR Range	Up to 40 m
Interface	
Video Output	1 HD analog output
General	
Power	12 VDC \pm 30%/PoC.af, max. 4W
Material	Plastic
Dimension	110 mm \times 93.2 mm (4.33" \times 3.67")
Weight	Approx. 350 g(0.77 lb.)
Operating Condition	-40 °C to 60 °C(-40 °F to 140 °F), humidity 90% or less(non-condensing)
Communication	HIKVISION-C
Language	English
Approval	
Protection	IP67