

# DS-2CE56D8T-IRS

Hikvision DS-2CE56D8T-IRS 2 MP TVI video kamera; Piksel 1920×1080; IR işıqlandırma - 20 m; F2,8 mm; Bucaq-94.5°; Mikrofon



Model	DS-2CE56D8T-IRS
Brend	Hikvision
Növ	Analoq
Meqapixel	2 MP
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8
İşıqlandırma	İR
İşıqlandırma məsafəsi	20 m
Material	Plastik

## Specification

Camera	
Image Sensor	2 megapixel progressive CMOSsensor
Signal System	PAL/NTSC
Frame Rate	PAL: 1080p@25fps NTSC: 1080p@30fps
Resolution	1920 (H) × 1080 (V)
Min. illumination	0.005 Lux@ (F1.2, AGC ON), 0Lux with IR
Shutter Time	PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s
Slow Shutter	Max. 16 times
Lens	2.8 mm, 3.6 mm, 6 mm fixed focal lens
Horizontal Fieldof View	94.5° (2.8mm), 79.1° (3.6 mm), 50° (6 mm)
Lens Mount	M12
Day & Night	IR cut filter
Angle Adjustment	Pan: -30° to 30°, Tilt: 0° to 80°, Rotate: -180° to 180°
Synchronization	Internal synchronization
Ture WDR	> 120 dB
Menu	

<b>AGC</b>	<b>Support</b>
<b>Day/Night Mode</b>	<b>Auto/Color/BW (Blackand White)</b>
<b>White Balance</b>	<b>ATW/MANUAL</b>
<b>Privacy Mask</b>	<b>ON/OFF, 4 programmable privacy masks</b>
<b>Motion Detection</b>	<b>4 programmable motion areas</b>
<b>Backlight Compensation</b>	<b>WDR/BLC/OFF</b>
<b>3D DNR (Digital Noise Reduction)</b>	<b>Level 1 to 10</b>
<b>Language</b>	<b>English, Chinese</b>
<b>Functions</b>	<b>Brightness, sharpness, mirror, smartIR</b>
<i>Interface</i>	
<b>Video Out</b>	<b>1 BNC</b>
<b>Audio In</b>	<b>Built-in microphone</b>
<b>Audio Out</b>	<b>1 RCA</b>
<i>General</i>	
<b>Operating Conditions</b>	<b>-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (no condensation)</b>
<b>Power Supply</b>	<b>12 VDC±30%</b>
<b>Power Consumption</b>	<b>Max. 5 W</b>
<b>Material</b>	<b>Metal &amp; plastic</b>
<b>IR Range</b>	<b>Up to 20 m</b>
<b>Dimensions</b>	<b>97 mm × 99.5mm × 46.6 mm (3.82" × 3.92" × 1.83")</b>
<b>Weight</b>	<b>Approx. 300 g (0.66lb.)</b>