

## DS-2CE70D0T-ITMF (AG)

Hikvision DS-2CE70D0T-ITMF (Ag) 2 mp meqapiksel TVI video kamera; Piksel 1920×1080; IR işıqlandırma - 20 m; F2,8 mm; Bucaq-106°;



### Specifications

Model	DS-2CE70D0T-ITMF (Ag)
Brand	Hikvision
Qoruma	IP67
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma məsafəsi	20 m
Obyektiv	Sabit
Fokus	2.8mm
İşıqlandırma	İR
Material	Metal
İstifadə mühiti	Indoor

## KEY FEATURES

**Camera****Image Sensor** 2 MP CMOS**Signal System** PAL/NTSC**Effective Pixels** 1920 (H) × 1080 (V)

TVI: 1080P@25fps, 1080P@30fps AHD: 1080P@25fps, 1080P@30fps CVI: 1080P@25fps, 1080P@30fps

**Frame Rate** CVBS: P/N**Min. Illumination** 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR**Shutter Time** PAL:1/25 s to 1/50,000 s NTSC:1/30 s to 1/50,000 s**Lens** 2.8 mm, 3.6mm, 6 mm fixed lens**Horizontal Fieldof View** 106° (2.8 mm), 80° (3.6 mm), 51° (6 mm)**Lens Mount** M12**Day & Night** ICR**WDR** Digital WDR**Angle Adjustment** Pan: 0° to 360°, Tilt:0° to 80°,Rotation: 0° to 360°**Menu****Image Mode** STD/HIGH-SAT**AGC** Yes**Day/Night Mode** Auto/Color/BW (Blackand White)**White Balance** Auto**AE (Auto Exposure) Mode** Global/BLC/HLC/DWDR**Noise Reduction** 2D DNR**Language** English**Function** Brightness, Sharpness, Mirror, Smart IR**Interface****Video Output** Switchable TVI/AHD/CVI/CVBS**General**

-40 °C to 60°C (non-condensing)

**Operating Conditions**

12 VDC ± 25%

**Power Supply***\*You are recommended to use one power adapter to supply the power forone camera.***Power Consumption** Max. 3.6 W**Protection Level** IP67**Material** Metal**IR Range** Up to 20 m**Communication** HIKVISION-C**Dimensions** Φ 61.12 mm × 60 mm (Φ 2.57" × 2.56")**Weight** 160 g (0.35 lb.)