

# DS-2CE70D0T-ITMF (Qara)

Hikvision DS-2CE70D0T-ITMF (Qara) 2 mp meqapiksel TVI video kamera; Piksel 1920×1080; IR işıqlandırma - 20 m; F2,8 mm; Bucaq-106°;

Model	DS-2CE70D0T-ITMF (Qara)
Brend	Hikvision
Qoruma	IP67
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma məsafəsi	20 m
Obyektiv	Sabit
Fokus	2.8mm
İşıqlandırma	İR
Material	Metal
İş mühiti	Indoor



## Specification

<i>Camera</i>	
Image Sensor	2 MP CMOS
Signal System	PAL/NTSC
Effective Pixels	1920 (H) × 1080 (V)
Frame Rate	TVI: 1080P@25fps, 1080P@30fps AHD: 1080P@25fps, 1080P@30fps CVI: 1080P@25fps, 1080P@30fps CVBS: P/N
Min. Illumination	0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL:1/25 s to 1/50,000 s NTSC:1/30 s to 1/50,000 s
Lens	2.8 mm, 3.6mm, 6 mm fixed lens
Horizontal Fieldof View	106° (2.8 mm), 80° (3.6 mm), 51° (6 mm)
Lens Mount	M12
Day & Night	ICR
WDR	Digital WDR
Angle Adjustment	Pan: 0° to 360°, Tilt:0° to 80°,Rotation: 0° to 360°
<i>Menu</i>	
Image Mode	STD/HIGH-SAT
AGC	Yes
Day/Night Mode	Auto/Color/BW (Blackand White)
White Balance	Auto
AE (Auto Exposure) Mode	Global/BLC/HLC/DWDR
Noise Reduction	2D DNR
Language	English
Function	Brightness, Sharpness, Mirror, Smart IR
<i>Interface</i>	

<b>Video Output</b>	Switchable TVI/AHD/CVI/CVBS
<i>General</i>	
<b>Operating Conditions</b>	-40 °C to 60 °C (non-condensing)
<b>Power Supply</b>	12 VDC ± 25% <i>*You are recommended to use one power adapter to supply the power for one camera.</i>
<b>Power Consumption</b>	Max. 3.6 W
<b>Protection Level</b>	IP67
<b>Material</b>	Metal
<b>IR Range</b>	Up to 20 m
<b>Communication</b>	HIKVISION-C
<b>Dimensions</b>	Φ 61.12 mm × 60 mm (Φ 2.57" × 2.56")
<b>Weight</b>	160 g (0.35 lb.)