

DS-2CE70KF0T-PFS

Hikvision DS-2CE70KF0T-PFS 4 mp meqapiksel TVI səsli ColorVu (rəngli) video kamera; Piksel 2960×1665; LED işıqlandırma - 20 m; F2.8 mm; Bucaq-102°; Audio (Mikrofon)



Specifications

Model	DS-2CE70KF0T-PFS
Brand	Hikvision
Material	Plastik
Növ	Analoq
Meqapixel	4 MP
İşıqlandırma	LED
Mikrofon	Mic
İşıqlandırma məsafəsi	20 m
Obyektiv	Sabit
Fokus	2.8mm
İşləmə mühiti	Indoor

KEY FEATURES

Camera	
Image Sensor	3K CMOS
Signal System	PAL/NTSC
Resolution	2960 (H) × 1665 (V)
	TVI: 3K@20fps, 4 MP@25fps/30fps, 1080p@25fps/30fps AHD: 5MP@20fps, 4 MP@25fps/30fps
	CVI: 4 MP@25fps/30fps
Frame Rate	CVBS: PAL/NTSC
Min. Illumination	0.001 Lux @ (F1.0, AGC ON), 0 Lux with whitelight
Shutter Time	PAL: 1/25 s to 1/50,000 s;NTSC: 1/30 s to 1/50,000 s
Lens	2.8 mm, 3.6 mm fixed focallens
Field of View	2.8 mm, horizontal FOV: 102°, vertical FOV: 56°, diagonal FOV: 122°
	3.6 mm, horizontal FOV:80°, vertical FOV: 45°, diagonal FOV: 96°
Lens Mount	M12
Light Alarm	Solid Light Alarm(White Light)
Day & Night	24/7 Color Imaging
WDR (Wide Dynamic Range)	Digital WDR
Angle Adjustment	Pan: 0° to 360°, Tilt:0° to 75°, Rotation: 0° to 360°
Image	
White Light	Auto/Off
Image Mode	STD/HIGH-SAT/HIGHLIGHT
AGC	Yes
Day/Night Mode	Color
White Balance	Auto/Outdoor/Global/Manual
AE (Auto Exposure) Mode	DWDR,BLC,HLC,Global,HLS
Noise Reduction	2D DNR
Language	English
Function	Brightness,Contrast,Mirror,Defective Pixel Correction,Sharpness,Anti-Banding,Smart Light
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS
Audio In	Built-in mic
General	
Operating Conditions	-40°C to 60°C (-40°Fto 140°F), Humidity: 90% or less(non-condensing)
Power Supply	12 VDC ± 25%,
Consumption	Max. 2.5 W
Material	Plastic
White LightRange	Up to 20 m
Communication	HIKVISION-C

Dimension	Φ 85.02 mm × 81.25mm (Φ 3.35" × 3.2")
Weight	Approx. 165.5 g (0.36 lb.)