

DS-2CE72DF3T-FS

Hikvision DS-2CE72DF3T-FS 2 MP ColorVu (rəngli) TVI video kamera; Piksel 1920×1080; Led işıqlandırma - 40 m; F2,8 mm; Bucaq-98°; WDR:130db; Mikrofon;



Specifications

Model	DS-2CE72DF3T-FS
Brand	Hikvision
?? mühiti	Indoor
Növ	Analoq
Meqapixel	2 MP
???qland?rma	LED
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8mm
???qland?rma m?saf?si	40 m
Qoruma	IP67
Material	Metal

KEY FEATURES

Camera	
Image Sensor	2 MP CMOS
Signal System	PAL/NTSC
Resolution	1920 (H) × 1080 (V)
	TVI: 1080p@25fps/30fps CVI: 1080p@25fps/30fps AHD: 1080p@25fps/30fps
Frame Rate	CVBS: PAL/NTSC
Min. Illumination	0.0005 Lux @ (F1.0, AGC ON), 0 Lux with white light ON
Shutter Time	PAL: 1/25s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
Slow Shutter	Max. 16 times
Lens	2.8 mm, 3.6 mm, 6mm Fixed Lens
	2.8 mm, horizontal FOV: 98°, vertical FOV: 52°, diagonal FOV: 116°
Field of View	3.6 mm, horizontal FOV: 77°, vertical FOV: 42°, diagonal FOV: 91°
	6 mm, horizontal FOV: 51°, vertical FOV: 28°, diagonal FOV: 59°
Lens Mount	M12
Light Alarm	Solid Light Alarm (White Light)
Day & Night	Color
WDR (Wide Dynamic Range)	≥130 dB
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360°
Menu	
White Light	Auto/Off
Image Mode	STD/HIGH-SAT/HIGHLIGHT
AGC	Yes
Day/Night Mode	Color
White Balance	Auto/Manual
AE (Auto Exposure) Mode	WDR, BLC, HLC, Global, HLS
Privacy Mask	4 programmable privacy masks
Motion Detection	4 programmable motion areas
Noise Reduction	3D DNR/2D DNR
Language	English
Function	Brightness, Contrast, Mirror, Defective Pixel Correction, Sharpness, Anti-Banding, Smart Light
Lighting Mode	White Light
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS
General	
Operating Conditions	-40°C to 60°C (-40°F to 140°F), Humidity: 90% or less (non-condensing)
Power Supply	12 VDC ± 25%, <i>*You are recommended to use one power adapter to supply the power for one camera.</i>
Consumption	Max. 4.2 W

Protection Level	IP67
Material	Main body: Metal,Enclosure: Plastic
White LightRange	Up to 40 m
Communication	HIKVISION-C
Dimension	Φ 109.98mm × 98.27 mm (Φ 4.33" × 3.87")
Weight	Approx. 348.5 g (0.77 lb.)