

DS-2CE72DF3T-PIRXOS

Hikvision DS-2CE72DFT-PIRXOF 2 MP ColorVu (rəngli) PIR TVI video kamera; Piksel 1920×1080; Led işıqlandırma - 20 m; F2,8 mm; Bucaq-98°;WDR:130dB



| | |
|-----------------------|---------------------|
| Model | DS-2CE72DF3T-PIRXOS |
| Brend | Hikvision |
| Növ | Analoq |
| Meqapixel | 2 MP |
| İşıqlandırma | LED |
| Obyektiv | Sabit |
| Fokus | 2.8 |
| İşıqlandırma məsafəsi | 20 m |
| Mikrofon | Mic |
| Qoruma | IP66 |
| Material | Metal |

Specification

| | |
|--------------------------|---|
| Camera | |
| Image Sensor | 2 MP CMOS |
| Signal System | PAL/NTSC |
| Resolution | 1920 (H) × 1080 (V) |
| Frame Rate | TVI: 1080p @ 25 fps/30 fps |
| Min. Illumination | 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with white light |
| Shutter Time | PAL: 1/25s to 1/50,000 s; NTSC: 1/30s to 1/50,000 s |
| Slow Shutter | Max. 16 times |
| Lens | 2.8 mm, 3.6mm fixed focallens |
| Field of View | 2.8 mm, horizontal FOV: 98°, vertical FOV: 52°, diagonal FOV: 116° 3.6 mm, horizontal FOV: 77°, vertical FOV: 42°, diagonal FOV: 91° |
| Lens Mount | M12 |
| Light Alarm | Flashing Light Alarm (Red & Blue) |
| Day & Night | Color |
| WDR (Wide Dynamic Range) | ≥130 dB |
| Angle Adjustment | Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360° |
| Menu | |
| White Light | Auto/Off |
| Image Mode | STD/HIGH-SAT/HIGHLIGHT |
| AGC | Yes |
| Day/Night Mode | Color |
| White Balance | Auto/Manual |
| AE (Auto Exposure) Mode | WDR, BLC, HLC, Global, HLS |
| Privacy Mask | 4 programmable privacy masks |

| | |
|----------------------|--|
| Motion Detection | 4 programmable motion areas |
| Noise Reduction | 3D DNR/2DDNR |
| Language | English |
| Function | Brightness, Contrast, Mirror, Defective Pixel Correction, Sharpness, Anti-Banding, Smart Light |
| Interface | |
| Video Output | 1 HD analog output |
| Alarm | 1 line out |
| Audio In | Built-in mic |
| General | |
| Operating Conditions | -40°C to 60°C (-40°F to 140°F), Humidity: 90% or less(non-condensing) |
| Power Supply | 12 VDC ± 25% <i>*You are recommended to use one power adapter to supply the power for one camera.</i> |
| Consumption | Max. 9.6 W |
| Protection Level | IP67 |
| Material | Main body: Metal, Enclosure: Plastic |
| White Light Range | Up to 20 m |
| PIR Range | Angle: 110°, Range: 11 m |
| Communication | HIKVISION-C |
| Dimension | Ø109.82 mm × 93.66mm (Ø4.3" × 3.7") |
| Weight | Approx. 396 g(0.87 lb.) |