

## DS-2CE72DF3T-PIRXOS

Hikvision DS-2CE72DFT-PIRXOF 2 MP ColorVu (rəngli) PIR TVI video kamera; Piksel 1920×1080; Led işıqlandırma - 20 m; F2,8 mm; Bucaq-98°;WDR:130dB



### Specifications

|                       |                     |
|-----------------------|---------------------|
| Model                 | DS-2CE72DF3T-PIRXOS |
| Brand                 | Hikvision           |
| ?? mühiti             | Indoor              |
| Növ                   | Analoq              |
| Meqapixel             | 2 MP                |
| ???qland?rma          | LED                 |
| Obyektiv              | Sabit               |
| Fokus                 | 2.8mm               |
| ???qland?rma m?saf?si | 20 m                |
| Mikrofon              | Mic                 |
| Qoruma                | IP66                |
| Material              | Metal               |

## KEY FEATURES

|                                 |   |
|---------------------------------|---|
| <b>Camera</b>                   |   |
| <b>Image Sensor</b>             | 2 MP CMOS   |
| <b>Signal System</b>            | PAL/NTSC  |
| <b>Resolution</b>               | 1920 (H) × 1080 (V)   |
| <b>Frame Rate</b>               | TVI: 1080p @ 25 fps/30 fps  |
| <b>Min. Illumination</b>        | 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with white light   |
| <b>Shutter Time</b>             | PAL: 1/25s to 1/50,000 s; NTSC: 1/30s to 1/50,000 s   |
| <b>Slow Shutter</b>             | Max. 16 times   |
| <b>Lens</b>                     | 2.8 mm, 3.6mm fixed focal lens  |
| <b>Field of View</b>            | 2.8 mm, horizontal FOV: 98°, vertical FOV: 52°, diagonal FOV: 116°<br>3.6 mm, horizontal FOV: 77°, vertical FOV: 42°, diagonal FOV: 91° |
| <b>Lens Mount</b>               | M12   |
| <b>Light Alarm</b>              | Flashing Light Alarm (Red & Blue)   |
| <b>Day &amp; Night</b>          | Color   |
| <b>WDR (Wide Dynamic Range)</b> | ≥130 dB   |
| <b>Angle Adjustment</b>         | Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360°  |
| <b>Menu</b>                     |   |
| <b>White Light</b>              | Auto/Off  |
| <b>Image Mode</b>               | STD/HIGH-SAT/HIGHLIGHT  |
| <b>AGC</b>                      | Yes   |
| <b>Day/Night Mode</b>           | Color   |
| <b>White Balance</b>            | Auto/Manual   |
| <b>AE (Auto Exposure) Mode</b>  | WDR, BLC, HLC, Global, HLS  |
| <b>Privacy Mask</b>             | 4 programmable privacy masks  |
| <b>Motion Detection</b>         | 4 programmable motion areas   |
| <b>Noise Reduction</b>          | 3D DNR/2DDNR  |
| <b>Language</b>                 | English   |
| <b>Function</b>                 | Brightness, Contrast, Mirror, Defective Pixel Correction, Sharpness, Anti-Banding, Smart Light  |
| <b>Interface</b>                |   |
| <b>Video Output</b>             | 1 HD analog output  |
| <b>Alarm</b>                    | 1 line out  |
| <b>Audio In</b>                 | Built-in mic  |
| <b>General</b>                  |   |
| <b>Operating Conditions</b>     | -40°C to 60°C (-40°F to 140°F), Humidity: 90% or less (non-condensing)  |
| <b>Power Supply</b>             | 12 VDC ± 25%  |
|                                 | <i>*You are recommended to use one power adapter to supply the power for one camera.</i>  |
| <b>Consumption</b>              | Max. 9.6 W  |
| <b>Protection Level</b>         | IP67  |
| <b>Material</b>                 | Main body: Metal, Enclosure: Plastic  |
| <b>White Light Range</b>        | Up to 20 m  |

---

|                      |  |
|----------------------|--|
| <b>PIR Range</b>     | <b>Angle: 110°, Range: 11 m</b>            |
| <b>Communication</b> | <b>HIKVISION-C</b>                         |
| <b>Dimension</b>     | <b>Ø109.82 mm × 93.66mm (Ø4.3" × 3.7")</b> |
| <b>Weight</b>        | <b>Approx. 396 g(0.87 lb.)</b>             |