

DS-2CE72DF3T-PIRXOS

Hikvision DS-2CE72DFT-PIRXOF 2 MP ColorVu (rəngli) PIR TVI video kamera; Piksel 1920×1080; Led işıqlandırma - 20 m; F2,8 mm; Bucaq-98°;WDR:130dB



Model	DS-2CE72DF3T-PIRXOS
Brend	Hikvision
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma	LED
Obyektiv	Sabit
Fokus	2.8
İşıqlandırma məsafəsi	20 m
Mikrofon	Mic
Qoruma	IP66
Material	Metal

Specification

Camera	
Image Sensor	2 MP CMOS
Signal System	PAL/NTSC
Resolution	1920 (H) × 1080 (V)
Frame Rate	TVI: 1080p @ 25 fps/30 fps
Min. Illumination	0.0005 Lux @ (F1.0, AGC ON), 0 Lux with white light
Shutter Time	PAL: 1/25s to 1/50,000 s; NTSC: 1/30s to 1/50,000 s
Slow Shutter	Max. 16 times
Lens	2.8 mm, 3.6mm fixed focal lens
Field of View	2.8 mm, horizontal FOV: 98°, vertical FOV: 52°, diagonal FOV: 116° 3.6 mm, horizontal FOV: 77°, vertical FOV: 42°, diagonal FOV: 91°
Lens Mount	M12
Light Alarm	Flashing Light Alarm (Red & Blue)
Day & Night	Color
WDR (Wide Dynamic Range)	≥130 dB
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 75°, Rotation: 0° to 360°
Menu	
White Light	Auto/Off
Image Mode	STD/HIGH-SAT/HIGHLIGHT

AGC	Yes
Day/Night Mode	Color
White Balance	Auto/Manual
AE (Auto Exposure) Mode	WDR, BLC, HLC, Global, HLS
Privacy Mask	4 programmable privacy masks
Motion Detection	4 programmable motion areas
Noise Reduction	3D DNR/2DDNR
Language	English
Function	Brightness, Contrast, Mirror, Defective Pixel Correction, Sharpness, Anti-Banding, Smart Light
Interface	
Video Output	1 HD analog output
Alarm	1 line out
Audio In	Built-in mic
General	
Operating Conditions	-40°C to 60°C (-40°F to 140°F), Humidity: 90% or less(non-condensing)
Power Supply	12 VDC ± 25% <i>*You are recommended to use one power adapter to supply the power for one camera.</i>
Consumption	Max. 9.6 W
Protection Level	IP67
Material	Main body: Metal, Enclosure: Plastic
White Light Range	Up to 20 m
PIR Range	Angle: 110°, Range: 11 m
Communication	HIKVISION-C
Dimension	Ø109.82 mm × 93.66mm (Ø4.3" × 3.7")
Weight	Approx. 396 g(0.87 lb.)