

DS-2CE76D0T-EXIMF

DS-2CE76D0T-EXIMF 2.8mm 2 MP IR 20m Fixed Turret Camera



Specifications

Model	DS-2CE76D0T-EXIMF
Brand	Hikvision
Qoruma	IP67
Növ	Analoq
Meqapixel	2 MP
??qland?rma m?saf?si	20 m
??qland?rma	IR
Obyektiv	Sabit
Fokus	2.8mm
Material	Metal
?? mühiti	Indoor

KEY FEATURES

Camera	
Model	DS-2CE76D0T-EXIMF
Product Name	2MP OutdoorEXIR Fixed TurretCamera
Image Sensor	2 MP CMOS
Signal System	PAL/NTSC
Resolution	1920 (H) × 1080 (V)
	TVI: 1080p@25fps/30fps AHD: 1080p@25fps/30fps CVI: 1080p@25fps/30fps
Frame Rate	CVBS: PAL/NTSC
Min. Illumination	0.02 Lux @ (F1.2, AGCON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s;NTSC: 1/30 s to 1/50,000 s
Lens	2.8 mm, 3.6 mm Fixed Lens
Field of View	2.8 mm, horizontal FOV: 96.5°, vertical FOV: 48.9°, diagonal FOV: 120.5° 3.6 mm, horizontal FOV: 76.9°, vertical FOV: 40.6°, diagonal FOV: 92.0°
Lens Mount	M12
Day & Night	IR Cut Filter
WDR (Wide DynamicRange)	Digital WDR
Angle Adjustment	Pan: 0° to 360°, Tilt:0° to 75°, Rotation: 0° to 360°
Image	
Image Mode	STD/HIGH-SAT
AGC	Yes
Day/Night Mode	Auto/Color/BW (Blackand White)
White Balance	Auto
AE (Auto Exposure) Mode	DWDR,BLC,Global
Noise Reduction	2D DNR
Language	English
Function	Brightness,Mirror,Smart IR,Sharpness
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS
General	
Operating Conditions	-40°C to 60°C (-40°Fto 140°F), Humidity: 90% or less(non-condensing)
Power Supply	12 VDC ± 25%
Consumption	Max. 3.3 W
Protection Level	IP67
Material	Metal
IR Range	Up to 20 m
Communication	HIKVISION-C
Dimension	90 mm × 82.6 mm × 79.372 mm (3.54" × 3.25" × 3.12")
Weight	Approx. 360g (0.79lb.)