

DS-2CE76D0T-EXIMF

DS-2CE76D0T-EXIMF 2.8mm 2 MP IR 20m Fixed Turret Camera



| | |
|-----------------------|-------------------|
| Model | DS-2CE76D0T-EXIMF |
| Brend | Hikvision |
| Qoruma | IP67 |
| Növ | Analoq |
| Meqapixel | 2 MP |
| İşıqlandırma məsafəsi | 20 m |
| İşıqlandırma | İR |
| Obyektiv | Sabit |
| Fokus | 2.8mm |
| Material | Metal |
| İş mühiti | Indoor |

Specification

| | |
|-------------------------|---|
| Camera | |
| Model | DS-2CE76D0T-EXIMF |
| Product Name | 2MP OutdoorEXIR Fixed TurretCamera |
| Image Sensor | 2 MP CMOS |
| Signal System | PAL/NTSC |
| Resolution | 1920 (H) x 1080 (V) |
| Frame Rate | TVI: 1080p@25fps/30fps AHD: 1080p@25fps/30fps CVI: 1080p@25fps/30fps CVBS: PAL/NTSC |
| Min. Illumination | 0.02 Lux @ (F1.2, AGCON), 0 Lux with IR |
| Shutter Time | PAL: 1/25 s to 1/50,000 s;NTSC: 1/30 s to 1/50,000 s |
| Lens | 2.8 mm, 3.6 mm Fixed Lens |
| Field of View | 2.8 mm, horizontal FOV: 96.5°, vertical FOV: 48.9°, diagonal FOV: 120.5° 3.6 mm, horizontal FOV: 76.9°, vertical FOV: 40.6°, diagonal FOV: 92.0° |
| Lens Mount | M12 |
| Day & Night | IR Cut Filter |
| WDR (Wide DynamicRange) | Digital WDR |
| Angle Adjustment | Pan: 0° to 360°, Tilt:0° to 75°, Rotation: 0° to 360° |
| Image | |
| Image Mode | STD/HIGH-SAT |
| AGC | Yes |

| | |
|-------------------------|--|
| Day/Night Mode | Auto/Color/BW (Blackand White) |
| White Balance | Auto |
| AE (Auto Exposure) Mode | DWDR,BLC,Global |
| Noise Reduction | 2D DNR |
| Language | English |
| Function | Brightness,Mirror,Smart IR,Sharpness |
| Interface | |
| Video Output | Switchable TVI/AHD/CVI/CVBS |
| General | |
| Operating Conditions | -40°C to 60°C (-40°Fto 140°F), Humidity: 90% or less(non-condensing) |
| Power Supply | 12 VDC ± 25% |
| Consumption | Max. 3.3 W |
| Protection Level | IP67 |
| Material | Metal |
| IR Range | Up to 20 m |
| Communication | HIKVISION-C |
| Dimension | 90 mm × 82.6 mm × 79.372 mm (3.54" × 3.25" × 3.12") |
| Weight | Approx. 360g (0.79lb.) |