

# DS-2CE76D0T-ITPFS

Hikvision DS-2CE76D0T-ITPFS 2 mp meqapiksel TVI video kamera; Piksel 1920×1080; IR işıqlandırma - 20 m; F2,8 mm; Bucaq-106.4°;



Model	DS-2CE76D0T-ITPFS
Brend	Hikvision
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma məsafəsi	20 m
Obyektiv	Sabit
Fokus	2.8
İşıqlandırma	İR
Qoruma	IP67
Material	Plastik

## Specification

Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.01 Lux @ (F2.0, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s
Day & Night	ICR
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 75°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm, 3.6 mm, 6 mm fixedlens
Focal Length & FOV	2.8 mm, horizontal FOV: 106.4°, vertical FOV: 57.9°, diagonal FOV: 124.6° 3.6 mm, horizontal FOV: 79.6°, vertical FOV: 43.5°, diagonal FOV: 93.7° 6 mm, horizontal FOV: 51.9°, vertical FOV: 30°, diagonal FOV: 58.8
Lens Mount	M12
Image	
Image Parameters Switch	STD/HIGH-SAT
Image Settings	Brightness, Sharpness, Mirror, Smart IR

<b>Frame Rate</b>	TVI: 1080P@30fps, 1080P@25fps AHD: 1080P@30fps, 1080P@25fps CVI: 1080P@30fps, 1080P@25fps CVBS: PAL/NTSC
<b>Day/Night Mode</b>	Auto/Color/BW (Black and White)
<b>Wide Dynamic Range (WDR)</b>	Digital WDR
<b>Image Enhancement</b>	Yes
<b>Image Enhancement</b>	Yes
<b>White Balance</b>	Auto/Manual
<b>AGC</b>	Support
<b>Interface</b>	
<b>Video Output</b>	Switchable TVI/AHD/CVI/CVBS
<b>General</b>	
<b>Material</b>	Plastic
<b>Dimension</b>	Φ 84.6 mm × 78.9 mm (Φ 3.33" × 3.11")
<b>Weight</b>	Approx. 140.5 g (0.31 lb.)
<b>Operating Condition</b>	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
<b>Communication</b>	HIKVISION-C
<b>Language</b>	English
<b>Power Supply</b>	12 VDC ± 25%
<b>Consumption</b>	Max. 2.7 W
<b>IR Range</b>	Up to 20 m