eurotech
Taste of technology

TEXNIKI SƏNƏD

29.11.2026

HIKVISION

DS-2CE76D0T-LPFS

Kod: 00-00002261 · Kamera



Hikvision DS-2CE76D0T-LPFS 2 mp Smart Light TVI video kamera; Piksel 1920×1080; IR işıqlandırma - 20 m; F2,8 mm; Bucaq-101°;

Texniki göstəricilər

Analoq Növ	**2 MP** Meqapixel
Mic Mikrofon	**20 m** İşıqlandırma məsafəsi
Sabit Obyektiv	**2.8mm** Fokus
İR İşıqlandırma	**IP67** Qoruma
Plastik Material	**Indoor** İş mühiti

Ətraflı məlumat

Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080(V)
Min. Illumination	0.01 Lux@ (F1.6, AGCON), 0 Lux with IR
Shutter Time	PAL: 1/25s to 1/50, 000 s; NTSC: 1/30s to 1/50, 000 s
Day &Night	ICR
Angle Adjustment	Pan: 0 to 360°,Tilt: 0 to 75°, Rotation: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm,3.6 mm fixedfocal lens
Focal Length& FOV	2.8 mm, horizontal FOV: 101°, vertical FOV: 56°, diagonal FOV: 118° 3.6 mm, horizontal FOV: 78°, vertical FOV: 42°, diagonal FOV: 92°
Lens Mount	M12
Microphone	
Pickup Distance	In a radius of up to 5 m
Amount	1
Illuminator	
Supplement LightRange	IR : Up to 20 m White Light: Up to 20 m
Supplement LightType	Smart, IR, White Light
Image	
Image Settings	Brightness, Sharpness, Smart IR
Frame Rate	TVI: 1080P @ 30 fps, 1080P @ 25 fps AHD: 1080P @ 30 fps, 1080P@ 25 fps CVI: 1080P @ 30 fps, 1080P @ 25 fps CVBS: PAL/NTSC

Wide Dynamic Range (WDR)	Digital WDR
Image Enhancement	DWDR/BLC/HLC/Global
White Balance	Auto/Manual
AGC	Yes
Day/Night Mode	Auto/Color
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS
General	
Material	Plastic
Dimension	84.6 mm × Ø85.02mm (3.33" × Ø3.35")
Weight	Approx. 156g (0.34 lb.)
Operating Condition	-40 °C to 60 °C (-40°F to 140 °F), humidity: 90% or less(non-condensation)
Communication	HIKVISION-C
Language	English
Power Supply	12 VDC ± 25% *You are recommended to use onepower adapter to supply the power for one camera.
Consumption	Max. 3.3 W

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az