eurotech
Taste of technology

TEXNIKI SƏNƏD

29.11.2026

HIKVISION

DS-2CE76D3T-ITMF

Kod: 00-00001390 · Kamera



Hikvision DS-2CE76D3T-ITMF 2 MP TVI video kamera; Piksel 1920×1080; IR işıqlandırma - 20 m; F2,8 mm; Bucaq-106°;WDR:120db;

Texniki göstəricilər

Analoq
Növ

2 MP
Meqapixel

30 m
İşıqlandırma məsafəsi

Sabit
Obyektiv

2.8mm
Fokus

İR
İşıqlandırma

Metal
Material

Indoor
İş mühiti

IP67
Qoruma

Ətraflı məlumat

Camera	
Image Sensor	2.0 megapixel progressive scanCMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.005 Lux@(F2.0, AGC ON), 0 Lux withIR
Shutter Time	PAL: 1/25 s to 1/50,000 s;NTSC: 1/30 s to 1/50,000 s
Day Night	IR Cut Filter
Angle Adjustment	Pan: 0° to 360°,Tilt: 0° to 75°, Rotation: 0° to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm, 3.6 mm, 6 mm
Focal Length FOV	106° (2.8 mm), 82° (3.6 mm), 51° (6 mm)
Lens Mount	M12
Illuminator	
Supplement LightType	IR
Supplement LightRange	Up to 30 m
Smart Supplement Light	Yes
Image	
Image Parameters Switch	STD/HIGH-SAT
Image Settings	Brightness,Mirror,Sharpness,AGC
Frame Rate	PAL: 1080p@25fps NTSC: 1080p@30fps
Day/Night Mode	Auto/Color/BW (Black and White)
Wide Dynamic Range (WDR)	≥120 dB
Image Enhancement	WDR,BLC,HLC
Noise Reduction	3D DNR

Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS,1 HD analog output
General	
Power	12 VDC ±25%, max. 4.6 W *You are recommended to use one power adapter to supply the power for one camera.
Material	Metal
Dimension	89.47 mm × 68.2mm (3.52" × 2.68")
Weight	Approx. 240 g (0.53lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less(non-condensation)
Language	English
Approval	
Protection	IP67

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az