

DS-2CE79D3T-IT3FZ

DS-2CE79D3T-IT3FZ 2.7-13.5 mm



Model	DS-2CE79D3T-IT3FZ
Brend	Hikvision
Qoruma	IP67
Növ	Analoq
Meqapixel	2 MP
Obyektiv	Motorized
Fokus	2.7 - 13.5mm
İşıqlandırma	İR
İşıqlandırma məsafəsi	70 m
Material	Metal
İş mühiti	Indoor

Specification

Camera	
Image Sensor	2.0 megapixel progressive scanCMOS
Max. Resolution	1920 (H) ×1080 (V)
Min. Illumination	0.005 Lux@(F1.6, AGC ON),0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s NTSC: 1/30 sto 1/50, 000 s
Day / Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°,Tilt: 0° to 75°, Rotation: 0° to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.7 mm to13.5 mm
Focal Length/ FOV	102° to 31°
Lens Mount	Φ 14
Image	
Image Parameters Switch	STD/HIGH-SAT
Image Settings	Brightness, Sharpness, 3D DNR, Mirror,Smart IR
Frame Rate	PAL: 1080p@25fps NTSC: 1080p@30fps
Day/Night Mode	Auto/Color/BW (Blackand White)
Wide Dynamic Range (WDR)	≥ 120 dB

Image Enhancement	BLC, HLC
White Balance	ATW/MWB
AGC	High/Medium/Low
Interface	
Video Output	1 HD analog output
Video Output	TVI/AHD/CVI/CVBS
General	
Material	Metal
Dimension	123.87 mm × 110.24 mm × 134.3mm (4.87" × 4.34" × 5.29")
Weight	Approx. 600 g(1.32 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less(non-condensation)
Language	English
Power Supply	12 VDC ±25% *You are recommended to use one power adapter to supply the power for one camera.
Consumption	Max. 7.7 W
IR Range	Up to 70 m
Approval	
Protection	IP67