

DS-2DE2C200SCG-E F0

Hikvision DS-2DE2C200SCG-E 2 MP ColorVu PT outdoor kamera üstün görüntü keyfiyyəti, 2.8mm - 4mm lens, 30 m smart white light və rəngli gecə görüntüsü ilə təmin edir. Pan (0–340°) və tilt (-5–105°) hərəkəti, daxili mikrofon-speaker, microSD dəstəyi (256 GB), PoE və IP66 qoruması ilə obyektlər üçün etibarlı təhlükəsizlik həllidir.



Specifications

Model	DS-2DE2C200SCG-E F0
Brand	Hikvision
Növ	IP
Meqapixel	2 MP
Obyektiv	PTZ
Fokus	2.8mm
???qland?rma	LED
???qland?rma m?saf?si	30 m
Mikrofon	Mic
Qoruma	IP66
Material	Plastik
Yadda?	MicroSD
?? mühiti	Outdoor

KEY FEATURES

Category	Specification
Image Sensor	1/2.7" Progressive Scan CMOS
Max. Resolution	1920 × 1080
Minimum Illumination	Color: 0.001 Lux @ (F1.0, AGC ON), 0 Lux with White Light
Lens Options	2.8 mm / 4 mm
FOV (2.8 mm)	H: 106.1° / V: 55.8° / D: 126.5°
FOV (4 mm)	H: 83.6° / V: 44.6° / D: 99.1°
Aperture	F1.0
Supplement Light Type	White Light
Range	Up to 30 m
Smart Light	Yes
Pan Range	0° to 340°
Tilt Range	-5° to 105°
Pan Speed	4°~21°/s (configurable)
Tilt Speed	4°~19°/s (configurable)
Main Stream	25 fps @ 50 Hz / 30 fps @ 60 Hz (1080p, 720p)
Sub-Stream	25 fps @ 50 Hz / 30 fps @ 60 Hz (640×480, 640×360)
Compression	H.265, H.264, MJPEG
Bitrate	32 Kbps – 8 Mbps
H.264 Profiles	Baseline / Main / High
H.265 Profile	Main
Compression	G.711a/u, G.722.1, G.726, MP2L2, AAC-LC, PCM
Bitrate	16~160 Kbps (depending on codec)
Sampling Rate	8 kHz / 16 kHz
Noise Filtering	Yes
Built-in Mic	Yes
Built-in Speaker	Yes
Protocols	IPv4/IPv6, HTTP/HTTPS, QoS, DNS/DDNS, NTP, RTSP/RTP, TCP/IP, UDP, DHCP, Bonjour
API	ONVIF, ISAPI, SDK
Settings	Brightness, contrast, saturation, sharpness
WDR	Digital WDR
Enhancements	BLC, HLC, 3D DNR
Network Port	RJ45 10/100M
Storage	microSD/SDHC/SDXC up to 256 GB
Reset Button	Yes
Basic Events	Motion, tampering, exception
Linkage	FTP upload, email, center notification, local storage
Power	12V DC (0.6A, max 7.2W) / PoE 802.3af (max 10W)
Camera Dimensions	162 × 120 × 234.2 mm
Package Dimensions	205 × 167 × 289 mm
Camera Weight	780 g

Category		Specification
Package Weight		1280 g
Operating Temp (Light ON)		-30°C to 40°C
Operating Temp (Light OFF)		-30°C to 50°C
Humidity		≤ 95% (non-condensing)
Functions		Mirror, password protection, watermark
Protection		IP66
Approvals		FCC, CE-EMC, IC, EN standards