

# DS-2SE4C225MWG-E/26F0

DS-2SE4C225MWG-E/26 F0 2mp IR 100m LED 30m TandemVu 6+2MP 25X Colorful & IR Panoramic & PTZ Camera H



## Specifications

Model	DS-2SE4C225MWG-E/26F0
Brand	Hikvision
Light source	LED
Lighting distance	30 m
Material	Plastik
Environment	Outdoor
Protocol	IP
Resolution	2 MP
Optical	PTZ
Protection	IP66
Storage	MicroSD

## KEY FEATURES

Camera	
Image Sensor	[Bullet channel]: 1/2.5" Progressive Scan CMOS;  [PTZchannel]: 1/2.8" progressive scan  CMOS
Max. Resolution	[Bullet channel] 3632 × 1632, [PTZ channel] 1920 × 1080  [Bullet channel]: 0.0005 Lux @ (F1.0, AGC ON),
Min. Illumination	0 Lux with light;  [PTZ channel]: Color: 0.005 Lux @ (F1.6,AGC ON),  B/W: 0.001 Lux @ (F1.6, AGC ON), 0  Lux with IR
Shutter Speed	1 s to 1/30,000 s
Slow Shutter	yes
Zoom	[PTZ channel] 25 × optical, 16 × digital
Day / Night	ICR
White Balance	auto,ATW,sodium lamp,fluorescent lamp,indoor,outdoor,MWB,Locked WB
Lens	
Focal Length	[Bullet channel]: 2.8 mm; [PTZchannel]: 4.8 to 120 mm, 25× optical
Zoom Speed	[PTZ channel]: approx. 3.6 s  [Bullet channel]: Horizontal field of view: 180±10°, Vertical field of view: 80±5°; [PTZ channel]:  Horizontal field of view: 54.8° to 2.8° (wide-tele), Vertical field of view:31.4° to 1.5° (wide-tele),  Diagonal field of view: 62.2°to 3.2° (wide-tele)
FOV	
Focus	semi-auto,manual,auto
Aperture	[Bullet channel]: F1.0; [PTZ channel]: F1.6
Illuminator	
Supplement Light Type	[PTZ channel]: IR; [Bullet channel]: White Light
Smart Supplement Light	Yes
Supplement LightRange PTZ	[PTZ channel]: up to 100 m; [Bulletchannel]: up to 30 m
Movement Range (Pan)	360°
Movement Range(Tilt)	-15° to 90° (auto flip)
Pan Speed	pan speed: configurable from0.1° to 80°/s;preset speed: 80°/s
Tilt Speed	tilt speed:configurable from 0.1° to 80°/s, presetspeed 80°/s
Proportional Zoom	yes
Presets	300
Patrol Scan	8 patrols, up to 32 presets for each patrol
Pattern Scan	4 pattern scans
Power-off Memory	yes

<b>Park Action</b>	<p>preset,pattern scan,patrol scan,auto scan,</p> <p>tilt scan,random scan,frame scan,panorama</p> <p>scan</p>
<b>3D Positioning</b>	yes
<b>PTZ Status Display</b>	yes
<b>Preset Freezing</b>	yes
<b>Scheduled Task</b>	<p>preset,pattern scan,patrol scan,auto scan,</p> <p>tilt scan,random scan,frame scan,panorama</p> <p>scan,dome reboot,dome adjust,aux output</p>
<b>User/Host</b>	32
<b>Security Measures</b>	<p>Authenticated username and password,</p> <p>MAC address binding,HTTPS encryption,802.1X</p> <p>authenticated access,IP address filter</p>
<b>Client</b>	iVMS-4200,Hik-Connect
<b>Image</b>	
<b>Image Settings</b>	sharpness, saturation, brightness, contrast
<b>Day/Night Switch</b>	day, night,auto, scheduled-switch
<b>Wide Dynamic Range (WDR)</b>	<p>[Bullet channel] Digital WDR</p> <p>[PTZ channel] 120 dB WDR</p>
<b>SNR</b>	≥ 52 dB
<b>Defog</b>	Digital defog
<b>Image Stabilization</b>	EIS
<b>Image Enhancement</b>	BLC,HLC,3D DNR
<b>Regional Focus</b>	Yes
<b>Regional Exposure</b>	Yes
<b>Image Parameters Switch</b>	Yes
<b>Privacy Mask</b>	<p>[Bullet channel] 8 programmable polygon privacy masks, [PTZ channel]24</p> <p>programmable polygon privacy masks; mask color or mosaic configurable</p>
<b>Interface</b>	
<b>Communication Interface</b>	RJ45, self-adaptive 10M/100M Ethernet port
<b>On-board Storage</b>	<p>Built-in memorycard slot, supportMicro SD</p> <p>/Micro SDHC/Micro SDXC, up to 256GB</p>
<b>Alarm Input</b>	1 alarm input
<b>Alarm Output</b>	1 alarm output
<b>Audio Input</b>	1 audio input,2.0 to 2.4Vp-p, 1k Ohm±10%
<b>Audio Output</b>	1 audio output, line level, impedance: 600 Ω
<b>Reset</b>	yes
<b>Event</b>	
<b>Basic Event</b>	<p>© 2026 Hikvision. All rights reserved.   Eurotechnology</p> <p>Motion detection,video tampering alarm,</p>