

DS-2SE7C124IW-AE

DS-2SE7C124IW-AE 4mm S5 Bullet 2mp IR 30m AcuSense PTZ 4mp 32x Optical Zoom
IR 200m smart tracking



Model	DS-2SE7C124IW-AE
Brend	Hikvision
Növ	IP
Meqapixel	2 MP
Obyektiv	PTZ
Fokus	4
İşıqlandırma	İR
İşıqlandırma məsafəsi	200m
Qoruma	IP66
Material	Metal

Specification

Smart functions (analytics):	Line Crossing/Area Intrusion/Loud Sound Detection/Area Intrusion
Audio compression:	G,711ulaw/G,711alaw/G,722,1/G,726/MP2L2
Motion Detector:	Program
Interfaces	RJ-45(F) x 1, AC/DC 24V x 1, Alarm input/output - 2/1, Audio input/output x 1/1
Protection class	IP66/IK10
Video encoding:	H.264 / H.264+ / H.265 / H.265+
Number of threads:	3 streams
Local storage:	Supports MicroSD/SDHC/SDXC memory cards up to 256 GB,
Housing material	Aluminium alloy
Camera setup:	WEB interface, NVR, DVR, SADP, IVMS-4200/4500/Hik-Central
Cloud service:	P2P Hik-Connect
Backlight	Smart up to 150m,
Power consumption	60 W, (maximum)
Permission	4.0MP (2560 x 1440)
Photosensitivity:	0.005 lux, @(F1.6, AGC on,), 0.001 lux, @(F1.6, AGC on,)
Sensor:	1/2.8" Progressive Scan CMOS
Transfer rate (bitrate):	from 32 Kb/sec, up to 16 Mb/sec,
Guarantee period	3 years
Operating temperature:	-30°C ~ +65°C
Device type	IP PTZ camera

Image enhancement:	WDR 120dB, 3D DNR, BLC, HLC, Defog, EIS, ROI
Electronic shutter:	from 1/1 to 1/30000 sec, (automatic, manual)
Power supply:	Hi-PoE (802.3at), AC 24V