

# DS-3E0106P-E/M

DS-3E0106P-E/M Hikvision unmanaged 4x100M POE+ switch, 2xEthernet Uplink ports, 35W POE budget



|             |                |
|-------------|----------------|
| Model       | DS-3E0106P-E/M |
| Brend       | Hikvision      |
| Port sayı   | 8 Port         |
| Port sürati | 100mb/s        |
| PoE         | PoE            |

## Specification

|                           |   |
|---------------------------|---|
| Model                     | DS-3E0106P-E/M                                      |
| Shell                     | Metal material                                      |
| Net Weight                | 0.27 kg (0.60lb)                                    |
| Gross Weight              | 0.52 kg (1.15lb)                                    |
| Dimensions (W x H x D)    | 145 mm x 68.45 mm x 25.6 mm (5.71" x 2.69" x 1.01") |
| Operating Temperature     | 0 °C to 40 °C (32 °F to 104 °F)                     |
| Storage Temperature       | -40 °C to 85 °C (-40 °F to 185 °F)                  |
| Operating Humidity        | 5% to 95% (no condensation)                         |
| Relative Humidity         | 5% to 95% (no condensation)                         |
| Power Supply              | 48 V DC, 0.8 A                                      |
| Max. Power Consumption    | 30 W  |
| Installation Mode         | Desk-Mounted,Wall-Mounted                           |
| Power Consumption in Idle | 3 W   |
| Surge Protection          | 6 kV  |
| Ports                     | 4 x 10/100 Mbps PoE port,2 x 10/100 Mbps RJ45 port  |
| MAC Address Table         | 2 K   |
| Switching Capacity        | 1.2 Gbps  |
| Packet Forwarding Rate    | 0.89 Mpps   |
| Internal Cache            | 768 Kbits   |
| PoE Standard              | IEEE 802.3af;IEEE 802.3at                           |

|                  |   |
|------------------|---|
| PoE Power Pin    | 8-pin power:1/2(-), 3/6(+), 4/5(+),7/8(-)   |
| PoE Port         | PoE: Ports1 to 4  |
| Max. Port Power  | 30 W  |
| PoE Power Budget | 35 W  |
| Long Range       | Ports 1 to 4: up to 300 m.<br>Long rangeperformance may varydepend on cameramodel or cablecondition.  |
| VIP Port         | Ports 1 to 2: data on VIP ports is preferentially forwarded when bandwidth resources are insufficient.  |
| EMC              | FCC (47 CFR Part15, Subpart B),CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019,EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011+A1: 2014, EN 55035: 2017+A11: 2020),IC (ICES-003: Issue7:2020),RCM (AS/NZS CISPR32: 2015) |
| Safety           | UL (UL 60950-1),CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition), CE-LVD(EN 62368-1: 2014+A11: 2017)  |
| Chemistry        | CE-RoHS (201165EU); WEEE (201219EU);<br>Reach (Regulation (EC)No.19072006)  |