

DS-3E0310P-E/M

Hikvision DS-3E0310P-E/M 8 port PoE switch, 110W ümumi PoE gücü və 60W Hi-PoE dəstəyi ilə kamera və şəbəkə avadanlıqları üçün etibarlı və yüksək performanslı enerji təmin edir. 2 Gigabit RJ45 uplink portları ilə sürətli və sabit bağlantı təmin edir.



Specifications

Model	DS-3E0310P-E/M
Brand	Hikvision
Port say?	8 Port
PoE	PoE
PoE gücü	100 W
Port sür?ti	100mb/s

KEY FEATURES

Category	Specification
General	
Shell	Metal material
Net Weight	0.555 kg (1.22 lb)
Gross Weight	1.20 kg (2.65 lb)
Dimensions (W × H × D)	217.6 mm × 103.35 mm × 27.8 mm (8.57" × 4.07" × 1.09")
Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
Storage Temperature	−40 °C to 85 °C (−40 °F to 185 °F)
Operating Humidity	5% to 95% (no condensation)
Relative Humidity	5% to 95% (no condensation)
Power Supply	48 VDC, 1.35 A
Max. Power Consumption	65 W
Power Consumption in Idle	5 W
Installation Mode	Desk-Mounted, Wall-Mounted
Surge Protection	6 KV
Network Parameters	
Ports	8 × 10/100 Mbps PoE ports, 2 × Gigabit RJ45 ports
MAC Address Table	8 K
Switching Capacity	5.6 Gbps
Packet Forwarding Rate	4.17 Mpps
Internal Cache	4 Mbits
PoE Power Supply	
PoE Standard	IEEE 802.3af; IEEE 802.3at
PoE Power Pin	8-pin power: 1/2(-), 3/6(+), 4/5(+), 7/8(-)
PoE Port	Ports 1 to 8
Max. Port Power	30 W
PoE Power Budget	60 W
Dialing Function	Long Range: Ports 1 to 8 up to 300 m (may vary depending on camera model or cable condition)
Approval	
EMC	FCC (47 CFR Part 15, Subpart B), CE-EMC (EN 55032:2015+A11:2020, EN IEC 61000-3-2:2019, EN 61000-3-3:2013+A1:2019, EN 50130-4:2011+A1:2014, EN 55035:2017+A11:2020), IC (ICES-003: Issue 7:2020), RCM (AS/NZS CISPR 32:2015)
Safety	UL (UL 60950-1), CB (AMD1:2009, AMD2:2013, IEC 62368-1:2014 Second Edition), CE-LVD (EN 62368-1:2014+A11:2017)
Chemistry	CE-RoHS (201165EU); WEEE (201219EU); REACH (Regulation (EC) No.1907/2006)