

DS-3E0318P-E/M(C)

DS-3E0318P-E/M C 16 Port Fast Ethernet Unmanaged POE Switch



Model	DS-3E0318P-E/M(C)
Brend	Hikvision
Port sayı	16 Port
Port sürəti	100mb/s
PoE	PoE
PoE gücü	120 W

Specification

Model	DS-3E0318P-E/M(B)
Port number	16 × 100 MbpsPoE ports, 1 × 1000Mbps RJ45 port,and 1 × 1000 Mbps SFP fiberoptical port
Port type	RJ45 port, fullduplex, MDI/MDI-X adaptive
Standard	IEEE 802.3,IEEE 802.3u, IEEE802.3x
Forwarding mode	Store-and-forward switching
Working mode	Standard mode(default); Extend mode
High priority ports	Ports 1 to 8
Ports for long-distance transmission	Ports 9 to 16
MAC address table	4 K
Switching capacity	7.2 Gbps
Packet forwarding rate	5.356 Mpps
Internal cache	2.75 Mbits
PoE standard	IEEE 802.3af, IEEE 802.3at
PoE power pin	1-16 support 8-corepower supply, Ethernet cable 1/2/3/6 and 4/5/7/8 provide simultaneous power supply.
PoE port	Ports 1 to 16
Max. port power	30 W
PoE power budget	130 W

Max. power consumption	150 W
Shell	Metal material
Gross weight	2.58 kg (5.69 lb)
Net weight	1.8 kg (4.0 lb)
Dimension (L x H x D)	266 mm x 44.5 mm x 220.8 mm (10.5" x 1.8" x 8.7")
Operating temperature	-10 °C to 55 °C(14 °F to 131 °F)
Storage temperature	-40 °C to 85 °C(-40 °F to 185 °F)
Operating humidity	5% to 95% (no condensation)
Storage humidity	5% to 95% (nocondensation)
Power supply	100 to 240 VAC, 50/60 Hz, Max. 2.5 A
Power consumption in idle	20 W
EMC	FCC (47 CFR Part 15, SubpartB); CE-EMC (EN 55032: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 55024: 2010+A1: 2015); RCM (AS/NZS CISPR32: 2015); IC (ICES-003: Issue6, 2016)
Safety	UL (UL 60950-1); CB (IEC60950-1:2005 + Am 1:2009 + Am 2:2013); CE-LVD (EN 60950-1:2005 + Am 1:2009+ Am 2:2013)
Chemistry	CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach(Regulation (EC) No 1907/2006)