

# DS-3E0318P-E/M(C)

DS-3E0318P-E/M C 16 Port Fast Ethernet Unmanaged POE Switch



## Specifications

Model	DS-3E0318P-E/M(C)
Brand	Hikvision
Port say?	16 Port
Port sür?ti	100mb/s
PoE	PoE
PoE gücü	120 W

## KEY FEATURES

<b>Model</b>	DS-3E0318P-E/M(B)
<b>Port number</b>	16 × 100 MbpsPoE ports, 1 × 1000Mbps RJ45 port, and 1 × 1000 Mbps SFP fiberoptical port
<b>Port type</b>	RJ45 port, full duplex, MDI/MDI-X adaptive
<b>Standard</b>	IEEE 802.3, IEEE 802.3u, IEEE 802.3x
<b>Forwarding mode</b>	Store-and-forward switching
<b>Working mode</b>	Standard mode(default); Extend mode
<b>High priority ports</b>	Ports 1 to 8
<b>Ports for long-distance transmission</b>	Ports 9 to 16
<b>MAC address table</b>	4 K
<b>Switching capacity</b>	7.2 Gbps
<b>Packet forwarding rate</b>	5.356 Mpps
<b>Internal cache</b>	2.75 Mbits
<b>PoE standard</b>	IEEE 802.3af, IEEE 802.3at
<b>PoE power pin</b>	1-16 support 8-core power supply, Ethernet cable 1/2/3/6 and 4/5/7/8 provide simultaneous power supply.
<b>PoE port</b>	Ports 1 to 16
<b>Max. port power</b>	30 W
<b>PoE power budget</b>	130 W
<b>Max. power consumption</b>	150 W
<b>Shell</b>	Metal material
<b>Gross weight</b>	2.58 kg (5.69 lb)
<b>Net weight</b>	1.8 kg (4.0 lb)
<b>Dimension (L × H × D)</b>	266 mm × 44.5 mm × 220.8 mm (10.5" × 1.8" × 8.7")
<b>Operating temperature</b>	-10 °C to 55 °C (14 °F to 131 °F)
<b>Storage temperature</b>	-40 °C to 85 °C (-40 °F to 185 °F)
<b>Operating humidity</b>	5% to 95% (no condensation)
<b>Storage humidity</b>	5% to 95% (no condensation)
<b>Power supply</b>	100 to 240 VAC, 50/60 Hz, Max. 2.5 A
<b>Power consumption in idle</b>	20 W
<b>EMC</b>	FCC (47 CFR Part 15, Subpart B); CE-EMC (EN 55032: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 55024: 2010+A1: 2015); RCM (AS/NZS CISPR32: 2015); IC (ICES-003: Issue 6, 2016)
<b>Safety</b>	UL (UL 60950-1); CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013); CE-LVD (EN 60950-1:2005 + Am 1:2009 + Am 2:2013)

---

**Chemistry**

**CE-RoHS (2011/65/EU); WEEE (2012/19/EU);**

**Reach(Regulation (EC) No 1907/2006)**