HIKVISION

DS-3E0520HP-E

Kod: 00-00005544 · Switchlər



Hikvision DS-3E0520HP-E 16-port gigabit unmanaged PoE switch-dir. 12 PoE port (30 W), 4 Hi-PoE port (90 W), 2 SFP və 2 RJ45 uplink portu var. Ümumi PoE büdcəsi 225 W. 300 m-ə qədər PoE ötürmə, port izolasiya, PoE watchdog və 6 kV qorunma funksiyaları ilə təhlükəsiz və geniş tətbiq olunan şəbəkə həlli təmin edir.

Texniki göstəricilər

16 Port	Port sayı
PoE	PoE
200 W	PoE gücü
1000mb/s	Port sürəti

Ətraflı məlumat

Category	Specification
Shell / Material	Metal
Net Weight	2.79 kg (6.15 lb)
Gross Weight	3.60 kg (7.94 lb)
Dimensions (W × H × D)	440 × 44 × 220.8 mm (17.3 × 1.7 × 8.7")
Operating Temperature	0–45°C (32–113°F)
Storage Temperature	-40–85°C (-40–185°F)
Operating Humidity	5–95% non-condensing
Relative Humidity	5–95% non-condensing
Power Supply	100–240 VAC, 50/60 Hz, Max. 4 A
Max Power Consumption	250 W
Power Consumption (Idle)	25 W
Installation Mode	Rackmount (with mounting ears)
Surge Protection	6 kV
Category	**Specification**
Ports	16 × Gigabit PoE, 2 × Gigabit RJ45, 2 × Gigabit fiber optical
MAC Address Table	8 K entries
Switching Capacity	40 Gbps
Packet Forwarding Rate	29.76 Mpps
Internal Cache	4.10 Mbits
Category	**Specification**
PoE Standard	IEEE 802.3af / 802.3at / 802.3bt

Category	Specification
PoE Power Pinout	1/2(-), 3/6(+), 4/5(+), 7/8(-)
PoE Ports	Hi-PoE: Ports 1–4 PoE: Ports 5–16
Max Port Power	90 W
PoE Power Budget	225 W
Long Range (Ports 13–16)	Up to 300 m (depends on camera model/cable)
Port Isolation	Ports 1–16: ports in an isolation group cannot communicate with each other, but can communicate with other ports outside the group
PoE Watchdog	Ports 1–16: auto-detect & restart unresponsive cameras
Category	**Specification**
EMC	FCC, CE-EMC, IC, RCM
Safety	UL 60950-1, CB, CE-LVD
Chemistry / RoHS	CE-RoHS (2011/65/EU)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az