

DS-3E0528HP-E

DS-3E0528HP-E 24 Port Gigabit Unmanaged POE Switch hikvision



Specifications

Model	DS-3E0528HP-E
Brand	Hikvision
Port say?	24 Port
PoE	PoE
PoE gücü	400 W
Port sür?ti	1000mb/s

KEY FEATURES

Model	DS-3E0528HP-E
Shell	Metal material
Net Weight	2.98 kg (6.57 lb)
Dimensions (W × H × D)	440.0 mm × 220.8 mm × 44.0 mm (17.32" × 8.69" × 1.73")
Operating Temperature	0 °C to 45 °C (32 °F to 113°F)
Storage Temperature	-40 °C to 85 °C (-40 °F to 185°F)
Operating Humidity	5% to 95% (no condensation)
Relative Humidity	5% to 95% (no condensation)
Power Supply	100~240 V AC, 50/60 Hz, Max. 6.5 A
Max. Power Consumption	400 W
Power Consumption in Idle	30 W
Installation Mode	Desk-Mounted
Surge Protection	6 kV
Ports	24 × Gigabit PoE port, 2 × Gigabit RJ45 port, 2 × Gigabit fiber optical port
MAC Address Table	8 K
Switching Capacity	56 Gbps
Packet Forwarding Rate	41.664 Mpps
Internal Cache	4.1 Mbits
PoE Standard	IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt
PoE Port	Hi-PoE: Ports 1 to 4 PoE: Ports 1 to 24
PoE Power Pin	8-pin power: 1/2(-), 3/6(+), 4/5(+), 7/8(-)
Max. Port Power	Ports 1 to 4: 90 W Ports 5 to 24: 30 W
PoE Power Budget	370 W
Long Range	Ports 21 to 24: upto 300 m. Long range performance may vary depend on camera model or cable condition. Ports 1 to 24: port isolation mode to improve network security.
Port Isolation	Ports in an isolation group cannot communicate with each other, but they can communicate with ports outside the isolation group.
PoE Watchdog	Ports 1 to 24: auto detect and restart the cameras that do not respond.
EMC	FCC (47 CFR Part 15, Subpart B), CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011+A1: 2014, EN 55035: 2017+A11: 2020), IC (ICES-003: Issue 7: 2020), RCM (AS/NZS CISPR32: 2015)

Safety

UL (UL 60950-1),CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014 (Second Edition), CE-LVD(EN 62368-1: 2014+A11: 2017)

Chemistry

CE-RoHS (2011/65/EU)