

DS-3E0528HP-E

DS-3E0528HP-E 24 Port Gigabit Unmanaged POE Switch hikvision



Model	DS-3E0528HP-E
Brend	Hikvision
Port sayı	24 Port
PoE	PoE
PoE gücü	400 W
Port sürati	1000mb/s

Specification

Model	DS-3E0528HP-E
Shell	Metal material
Net Weight	2.98 kg (6.57 lb)
Dimensions (W x H x D)	440.0 mm x 220.8 mm x 44.0 mm (17.32" x 8.69" x 1.73")
Operating Temperature	0 °C to 45 °C (32 °F to 113°F)
Storage Temperature	-40 °C to 85 °C (-40 °F to 185°F)
Operating Humidity	5% to 95% (no condensation)
Relative Humidity	5% to 95% (no condensation)
Power Supply	100~240 V AC, 50/60 Hz, Max. 6.5 A
Max. Power Consumption	400 W
Power Consumption in Idle	30 W
Installation Mode	Desk-Mounted
Surge Protection	6 kV
Ports	24 x Gigabit PoE port, 2x Gigabit RJ45port, 2 x Gigabitfiber optical port
MAC Address Table	8 K
Switching Capacity	56 Gbps
Packet Forwarding Rate	41.664 Mpps
Internal Cache	4.1 Mbits
PoE Standard	IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt

PoE Port	Hi-PoE: Ports 1 to 4 PoE: Ports 1 to 24
PoE Power Pin	8-pin power: 1/2(-), 3/6(+), 4/5(+), 7/8(-)
Max. Port Power	Ports 1 to 4: 90 W Ports 5 to 24: 30 W
PoE Power Budget	370 W
Long Range	Ports 21 to 24: upto 300 m. Long range performance may vary depend on camera model or cable condition.
Port Isolation	Ports 1 to 24: port isolation mode to improve network security. Ports in an isolation group cannot communicate with each other, but they can communicate with ports outside the isolation group.
PoE Watchdog	Ports 1 to 24: auto detect and restart the cameras that do not respond.
EMC	FCC (47 CFR Part 15, Subpart B), CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011+A1: 2014, EN 55035: 2017+A11: 2020), IC (ICES-003: Issue 7: 2020), RCM (AS/NZS CISPR 32: 2015)
Safety	UL (UL 60950-1), CB (AMD1: 2009, AMD2: 2013, IEC 62368-1: 2014 (Second Edition), CE-LVD (EN 62368-1: 2014+A11: 2017)
Chemistry	CE-RoHS (2011/65/EU)