HIKVISION

DS-3E1326P-EI

Kod: 00-00000563 · Switchlər



DS-3E1326P-EI 24p Unmanaged Fast Ethernet Smart POE Switch HIKVISION

Texniki göstəricilər

24 Port
Port sayı

Smart
Tip

PoE
PoE

400 W
PoE gücü

100mb/s
Port sürəti

Ətraflı məlumat

General	
Shell	Metal material
Net Weight	2.83 kg (6.24 lb)
Gross Weight	3.8 kg (8.38 lb)
Dimensions (W × H × D)	440.00 mm × 44.00 mm × 220.80 mm (17.32'' × 1.73'' × 8.69'')
Operating Temperature	0 °C to 45 °C (0 °F to 113 °F)
Storage Temperature	-40 °C to 85 °C (-40 °F to 185°F)
Operating Humidity	5% to 95% (no condensation)
Relative Humidity	5% to 95% (no condensation)
Power Supply	100-240 V AC, 50/60 Hz, Max. 6.3 A
Max. Power Consumption	400 W
Installation Mode	Rack (equipped with mounting ears)
Power Consumption in Idle	30 W
Surge Protection	6 kV
Network Parameters	
Ports	24 × 10/100 Mbps PoE port,2× Gigabit combo
MAC Address Table	16 K
Switching Capacity	Whole-Device Performance: 14.8 Gbps Port Performance: 8.8 Gbps
Packet Forwarding Rate	Whole-Device Performance: 11.01 Mpps Port Performance: 6.55 Mpps
Internal Cache	4 Mbits
PoE Power Supply	
PoE Standard	IEEE 802.3af,IEEE 802.3at
PoE Power Pin	8-pin power:1/2(-), 3/6(+), 4/5(+), 7/8(-)

PoE Port	PoE: Ports1 to 24
Max. Port Power	30 W
PoE Power Budget	370 W
Software Function	
Long Range	Ports 1 to 24: up to 300 m. Long rangeperformance may vary depend on camera model or cable condition.
VIP Port	Ports 1 to 8: data on VIP portsis preferentially forwarded when bandwidth resources are insufficient.
Port Isolation	Ports 1 to 24: port isolation mode to improvenetwork security Ports in an isolation group cannot communicate with each other,but they can communicate with ports outside the isolation group.
PoE Watchdog	Ports 1 to 24: auto detectand restart the cameras that do not respond.
Link Aggregation	Link aggregation is used to aggregate multiple physical ports to form a logical portfor load balancing, bandwidth expansion, and port protection. Support static linkaggregation. Support 1 aggregation group.
Loop Prevention	Loop prevention is used to prevent theswitching network fromforming loops, which will seriously affect network communication. Disabled by default. Support 802.1D STP. Suppport 802.1wRSTP.
VLAN	VLAN is usedfor network scaleplanning and network health improvement. Support 802.1Q. Configurable VLAN ID from 1-4094. Support Trunk,Access port mode. Support Max. 4094 VLAN.

HPP	Support one-click activation and remotemanagement via Hik-Partner Pro. Functions supported: 1. Display the port rate. 2. Display the port bandwidth utilization rate. 3. Display the PoE power usage. 4. Display topology information. 5. Display the alarm status. 6. Restart portsand devices. 7. Enable port long-rage mode. 8. Remotely upgrade the device.
System Maintenance	Support device management via web. Support DHCP Client.Enabled by defaultfor dynamic assignment of management IP addresses. Support Super IP,which is a fixed IP address (10.180.190.200) for direct access. Support management via Hik-Central Pro. Support remotemanagement via Hik-Partner Pro. Support cable detection. Abnormal open circuits and short circuits as well as network cable length can be detected. Supports 802.1ab LLDPfor peer device discovery. Support portmirroring for faultlocating.
Approval	
EMC	CE-EMC (EN 55032: 2015+A11: 2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1: 2019, EN 50130-4: 2011+A1: 2014, EN 55035:2017+A11: 2020),IC (ICES-003: Issue 7:2020),RCM (AS/NZS CISPR 32: 2015)
Safety	CB (AMD1:2009, AMD2:2013, IEC 62368-1: 2014(Second Edition)), CE-LVD(EN 62368-1: 2014+A11: 2017)
Chemistry	CE-RoHS (2011/65/EU),WEEE (2012/19/EU),Reach (Regulation (EC) No.1907/2006)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az