

DS-7104HGHI-K1

Hikvision DS-7104HGHI-K1 4 kanal xvr, 2 meqapiksel, 1 HDD, maks 4 TB HDD həcmi. 5 kanala qədər IP kamera girişləri və hər bir kanal 2 MP-ə qədər dəstəkləyir.



Specifications

Model	DS-7104HGHI-K1
Brand	Hikvision
Növ	XVR
Kanal say?	4 kanal
Meqapixel	2 MP
Max HDD say?	1 HDD

KEY FEATURES

Motion Detection 2.0

Deep learning-based motiondetection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights;

Human/Vehicle Analysis

Quick search by object or event typeis supported;

Recording

Video Compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264

For 1080p streamaccess: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF For 720p stream access: 720p/WD1/4CIF/VGA/CIF

For SD stream access:WD1/4CIF/VGA/CIF

Encoding Resolution

Main stream:

For 1080p streamaccess: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF@25 fps(P)/30 fps (N) For 720p stream access: 720p/WD1/4CIF/VGA/CIF@ 25fps (P)/30 fps (N)

For SD stream access: WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) Sub-stream:

4CIF@15fps; CIF/QVGA@25 fps (P)/30 fps(N)

Frame Rate

Video Bitrate 32 Kbps to 4 Mbps

Stream Type Video, Video &Audio

Audio Compression G.711u

Audio Bitrate 64 Kbps

Video and Audio

1-ch (upto 5-ch)

Up to 1080p resolution

IP Video Input Support H.265+/H.265/H.264+/H.264 IP cameras

4-ch

Analog VideoInput BNC interface (1.0 Vp-p,75 Ω), supporting coaxitron connection

HDTV Input 1080p25, 1080p30, 720p25, 720p30

AHD Input 1080p25, 1080p30, 720p25, 720p30

HDCVI Input 1080p25, 1080p30, 720p25, 720p30

CVBS Input Support

HDMI Output 1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280× 720/60Hz

VGA Output 1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280× 720/60Hz

Video OutputMode HDMI/VGA simultaneous output

	1-ch RCA (2.0Vp-p, 1 KΩ)
Audio Input	4-ch via coaxial cable
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Two-Way Audio	Reuse the first audio input
Synchronous playback	4-ch
Network	
Total Bandwidth	64 Mbps
Network Protocol	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP™, HTTPS
Remote Connection	32
Network Interface	1, RJ45 10/100Mbps self-adaptive Ethernet interface
Auxiliary Interface	
SATA	1 SATA interface
Capacity	Up to 4 TB capacity for each disk
USB Interface	Rear panel: 2 × USB 2.0
Alarm In/Out	N/A
General	
Power Supply	12 VDC, 1.5 A
Consumption	≤ 16 W (without HDD)
Working Temperature	-10 °C to 55 °C (14 °F to +31 °F)
Working Humidity	10% to 90%
Dimension (W × D × H)	200 × 200 × 45 mm (7.9 × 7.9 × 1.8 inch)
Weight	≤ 0.8 kg (without HDD, 1.8 lb.)