

DS-7104HGHI-K1

Hikvision DS-7104HGHI-K1 4 kanal xvr, 2 meqapiksel, 1 HDD, maks 4 TB HDD həcmi. 5 kanala qədər IP kamera girişləri və hər bir kanal 2 MP-ə qədər dəstəkləyir.



| | |
|--------------|----------------|
| Model | DS-7104HGHI-K1 |
| Brend | Hikvision |
| Növ | XVR |
| Kanal sayı | 4 kanal |
| Meqapixel | 2 MP |
| Max HDD sayı | 1 HDD |

Specification

| | |
|------------------------|---|
| Motion Detection 2.0 | |
| | Deep learning-based motiondetection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights; |
| Human/Vehicle Analysis | Quick search by object or event types supported; |
| Recording | |
| Video Compression | H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 |
| Encoding Resolution | For 1080p streamaccess: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF For 720p stream access: 720p/WD1/4CIF/VGA/CIF For SD stream access:WD1/4CIF/VGA/CIF |
| Frame Rate | Main stream: For 1080p streamaccess: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF@25 fps(P)/30 fps (N) For 720p stream access: 720p/WD1/4CIF/VGA/CIF@ 25fps (P)/30 fps (N) For SD stream access: WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) Sub-stream: 4CIF@15fps; CIF/QVGA@25 fps (P)/30 fps(N) |
| Video Bitrate | 32 Kbps to 4 Mbps |
| Stream Type | Video, Video &Audio |
| Audio Compression | G.711u |
| Audio Bitrate | 64 Kbps |
| Video and Audio | |
| IP Video Input | 1-ch (upto 5-ch) Up to 1080p resolution Support H.265+/H.265/H.264+/H.264 IP cameras |

| | |
|--------------------|---|
| Analog Video Input | 4-ch BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection |
| HDTV Input | 1080p25, 1080p30, 720p25, 720p30 |
| AHD Input | 1080p25, 1080p30, 720p25, 720p30 |
| HDCVI Input | 1080p25, 1080p30, 720p25, 720p30 |
| CVBS Input | Support |
| HDMI Output | 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz |
| VGA Output | 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz |
| Video Output Mode | HDMI/VGA simultaneous output |
| Audio Input | 1-ch RCA (2.0Vp-p, 1 KΩ) 4-ch via coaxial cable |

| | |
|-----------------------|--|
| Audio Output | 1-ch, RCA (Linear, 1 KΩ) |
| Two-Way Audio | Reuse the first audio input |
| Synchronous playback | 4-ch |
| Network | |
| Total Bandwidth | 64 Mbps |
| Network Protocol | TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP™, HTTPS |
| Remote Connection | 32 |
| Network Interface | 1, RJ45 10/100Mbps self-adaptive Ethernet interface |
| Auxiliary Interface | |
| SATA | 1 SATA interface |
| Capacity | Up to 4 TB capacity for each disk |
| USB Interface | Rear panel: 2 × USB 2.0 |
| Alarm In/Out | N/A |
| General | |
| Power Supply | 12 VDC, 1.5 A |
| Consumption | ≤ 16 W (without HDD) |
| Working Temperature | -10 °C to 55 °C (14 °F to +31 °F) |
| Working Humidity | 10% to 90% |
| Dimension (W × D × H) | 200 × 200 × 45 mm (7.9 × 7.9 × 1.8 inch) |
| Weight | ≤ 0.8 kg (without HDD, 1.8 lb.) |