

DS-7104HGHI-M1

Hikvision DS-7104HGHI-M1 HD-TVI DVR 4-kanallı video giriş dəstəyi ilə təhlükəsizliyi artırır. Yüksək keyfiyyətli qeyd, asan idarəetmə və uzaqdan nəzarət funksiyaları ilə kiçik ofis və ev üçün ideal həll təqdim edir.



Specifications

Model	DS-7104HGHI-M1
Brand	Hikvision
Növ	XVR
Kanal say?	4 kanal
Meqapixel	2 MP
Max HDD say?	1 HDD
Max HDD h?cmi	4 TB

KEY FEATURES

Category	Specification
Motion Detection 2.0	Deep learning-based; human/vehicle classification; reduces false alarms; quick search by object/event type
Video Input	IP: 1-ch (up to 5-ch), up to 1080p, supports H.265+/H.265/H.264+/H.264 IP cameras Analog: 4-ch (BNC 1.0 Vp-p, 75 Ω, coaxitron supported) HDTVI: 1080p25/1080p30/720p25/720p30 AHD: 1080p25/1080p30/720p25/720p30 HDCVI: 1080p25/1080p30/720p25/720p30 CVBS: Support
Video Output	HDMI: 1-ch, 1080p/60Hz, 1280×1024/60Hz, 1280×720/60Hz VGA: 1-ch, 1080p/60Hz, 1280×1024/60Hz, 1280×720/60Hz HDMI/VGA simultaneous output
Audio	Input: 1-ch RCA (2.0 Vp-p, 1 KΩ), 4-ch via coax Output: 1-ch RCA Linear 1 KΩTwo-way: reuse first input Compression: G.711u, Bitrate: 64 Kbps
Recording	Video compression: H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 Encoding resolution: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF; Sub-stream: 4CIF@15fps; CIF/QVGA@25/30fps Video bitrate: 32 Kbps to 4 Mbps Stream type: Video, Video & Audio
Synchronous Playback	4-ch
Network	Total bandwidth: 64 Mbps Protocol: TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP™, HTTPS Remote connection: 32Interface: 1 × RJ45 10/100 Mbps
Storage & Interfaces	SATA: 1 × interface, up to 4 TB per disk USB: 2 × USB 2.0 (rear panel)Alarm: N/A

Category	Specification
General	Power: 12 VDC, 1.5 A Consumption: ≤ 16 W (without HDD)Working temp: -10 °C to 55 °C Working humidity: 10–90 % Dimensions (W × D × H): 200 × 200 × 48 mm (7.9 × 7.9 × 1.9 in) Weight: ≤ 0.8 kg (without HDD, 1.8 lb.)