

# DS-7104HQHI-K1

## DS-7104HQHI-K1 2MP HD TVI DIGITAL VIDEO RECORDER HIKVISION



Model	DS-7104HQHI-K1
Brend	Hikvision
Növ	XVR
Kanal sayı	4 kanal
Meqapixel	2 MP
Max HDD sayı	1 HDD
Max HDD həcmi	4 TB

## Specification

Model	DS-7104HQHI-K1
Video compression	H.265+/H.265/H.264+/H.264
Analog video input	4-ch BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection
HDTVl input	3 MP, 1080p25, 1080p30, 720p25, 720p30, 720p50, 720p60 Note: The 3 MP signal input is only available for channel 1 of DS-7104HQHI-K1,
AHD input	1080p25, 1080p30, 720p25, 720p30
HDCVI input	1080p25, 1080p30, 720p25, 720p30
CVBS input	Support
IP videoinput	1-ch Up to 4 MP resolution Supports H.265+/H.265/H.264+/H.264 IP cameras
Audio compression	G.711u
Audio input/Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 KΩ)
HDMI/VGA output	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz

Encoding resolution	<p>When 1080p Lite mode not enabled: 3 MP/1080p/720p/WD1/4CIF/VGA/CIF;</p> <p>When 1080p Lite mode enabled: 3 MP/1080p lite/720p lite/WD1/4CIF/VGA/CIF</p>
Frame rate	<p>Main stream:</p> <p>When 1080p Lite mode not enabled: For 3 MP stream access: 3 MP/1080p/720p/VGA/WD1/4CIF/CIF@15fps For 1080p stream access: 1080p/720p@15fps; VGA/WD1/4CIF/CIF@25fps (P)/30fps (N) For 720p stream access: 720p/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N)</p> <p>When 1080p Lite mode enabled: 3 MP@15fps 1080p lite/720p lite/VGA/WD1/4CIF/CIF@25fps(P)/30fps (N)</p> <p>Sub-stream: WD1/4CIF@12fps; CIF@25fps (P)/30fps (N)</p>
Video bit rate	32 Kbps to 6 Mbps
Audio output	1-ch, RCA (Linear, 1 KΩ)
Audio bit rate	64 Kbps
Dual stream	Support
Stream type	Video, Video & Audio
Synchronous playback	4-ch
Remote connections	128
Network protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
SATA	1 SATA interface
Capacity	Up to 4 TB capacity for each disk
Network interface	1, RJ45 10M/100M self-adaptive Ethernet interface
USB interface	Real panel: 2 × USB 2.0
Power supply	12 VDC
Consumption (without HDD)	≤ 8 W
Working temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Working humidity	10% to 90%
Dimensions (W × D × H)	200 × 200 × 45 mm (7.9 × 7.9 × 1.8 inch)
Weight (without HDD)	≤ 1 kg (2.2 lb)