

# DS-7104NI-Q1/4P

DS-7104NI-Q1/4P NETWORK POE DIGITAL VIDEO RECORDER HIKVISION



## Specifications

Model	DS-7104NI-Q1/4P
Brand	Hikvision
Növ	NVR
Kanal say?	4 kanal
PoE d?st?yi	PoE
Meqapixel	5 MP
Max HDD say?	1 HDD
Max HDD h?cmi	6 TB

## KEY FEATURES

## Video and Audio

<b>IP Video Input</b>	<b>4-ch</b>
	<b>Up to 6 MP resolution</b>
<b>Incoming Bandwidth</b>	<b>40 Mbps</b>
<b>Outgoing Bandwidth</b>	<b>60 Mbps</b>
<b>HDMI Output</b>	<b>1-ch, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz</b>
<b>VGA Output</b>	<b>1-ch, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz</b>
<b>Video OutputMode</b>	<b>HDMI/VGA simultaneous output</b>
<b>Decoding</b>	
<b>Decoding Format</b>	<b>H.265+/H.265/ H.264+/H.264</b>
<b>Recording Resolution</b>	<b>6 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF</b>
<b>Synchronous playback</b>	<b>4-ch</b>
<b>Decoding Capability</b>	<b>4-ch@1080p (30 fps) or 2-ch@4 MP (30 fps) or 1-ch@6 MP (30 fps)</b>
<b>Stream Type</b>	<b>Video, Video&amp; Audio</b>
<b>Network</b>	
<b>Remote Connection</b>	<b>16</b>
<b>Network Protocol</b>	<b>TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP™</b>
<b>Network Interface</b>	<b>1, RJ-45 10/100Mbps self-adaptive Ethernet interface</b>
<b>PoE</b>	
<b>Interface</b>	<b>4, RJ-45 10/100 Mbps self-adaptive Ethernet interface</b>
<b>Power</b>	<b>≤ 36 W</b>
<b>Standard</b>	<b>IEEE 802.3af/at</b>
<b>Auxiliary Interface</b>	
<b>SATA</b>	<b>1 SATA interface</b>
<b>Capacity</b>	<b>Up to 6TB capacity for each disk</b>
<b>Alarm In/Out</b>	<b>N/A</b>
<b>USB Interface</b>	<b>Rear panel: 2 × USB 2.0</b>
<b>General</b>	
<b>Power Supply</b>	<b>48 VDC, 1 A</b>
<b>Consumption</b>	<b>≤ 10 W</b>
<b>Working Temperature</b>	<b>-10 to +55° C (+14 to +131° F)</b>
<b>Working Humidity</b>	<b>10% to 90%</b>
<b>Dimension (W × D × H)</b>	<b>200 × 200 × 48 mm (7.9" × 8.1" × 1.9")</b>
<b>Weight</b>	<b>≤ 1 kg (2.2lb)</b>
<b>Certification</b>	
<b>CE</b>	<b>EN50130-4, EN 61000-3-2, EN 61000-3-3</b>