

DS-7104NI-Q1/4P

DS-7104NI-Q1/4P NETWORK POE DIGITAL VIDEO RECORDER HIKVISION



Model	DS-7104NI-Q1/4P
Brend	Hikvision
Növ	NVR
Kanal sayı	4 kanal
PoE dəstəyi	PoE
Meqapixel	5 MP
Max HDD sayı	1 HDD
Max HDD həcmi	6 TB

Specification

Video and Audio	
IP Video Input	4-ch Up to 6 MP resolution
Incoming Bandwidth	40 Mbps
Outgoing Bandwidth	60 Mbps
HDMI Output	1-ch, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
VGA Output	1-ch, 1920 × 1080p/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
Video OutputMode	HDMI/VGA simultaneous output
Decoding	
Decoding Format	H.265+/H.265/ H.264+/H.264
Recording Resolution	6 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF
Synchronous playback	4-ch
Decoding Capability	4-ch@1080p (30 fps) or 2-ch@4 MP (30 fps) or 1-ch@6 MP (30 fps)
Stream Type	Video, Video& Audio
Network	
Remote Connection	16
Network Protocol	TCP/IP, DHCP,Hik-Connect, DNS, DDNS,NTP, SADP, SMTP,UPnP™

Network Interface	1, RJ-45 10/100Mbps self-adaptive Ethernet interface
PoE	
Interface	4, RJ-45/100 Mbps self-adaptive Ethernet interface
Power	≤ 36 W
Standard	IEEE 802.3af/at
Auxiliary Interface	
SATA	1 SATAinterface
Capacity	Up to 6TB capacity for each disk
Alarm In/Out	N/A
USB Interface	Rear panel:2 × USB 2.0
General	
Power Supply	48 VDC,1 A
Consumption	≤ 10 W
Working Temperature	-10 to +55° C (+14 to +131° F)
Working Humidity	10% to 90%
Dimension (W × D × H)	200 × 200 × 48 mm (7.9" × 8.1" × 1.9")
Weight	≤ 1 kg (2.2lb)
Certification	
CE	EN50130-4, EN 61000-3-2,EN 61000-3-3