

DS-7108HGHI-K1

Hikvision DS-7108HGHI-K1 8 kanal xvr, 2 meqapiksel, 1 HDD, maks 4 TB HDD h?cmi. 10 kanala q?d?r IP kamera giri?l?ri v? h?r bir kanal 2 MP-? q?d?r d?st?kl?yir.



Specifications

Model	DS-7108HGHI-K1
Brand	Hikvision
N?v	XVR
Kanal say?	8 kanal
Meqapixel	2 MP
Max HDD say?	1 HDD
Max HDD h?cmi	4 TB

KEY FEATURES

Motion Detection 2.0

Deep learning-based motion detection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights;

Human/Vehicle Analysis Quick search by object or event type is supported;

Recording

Video Compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264

For 1080p stream access: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF For 720p stream access: 720p/WD1/4CIF/VGA/CIF

For SD stream access: WD1/4CIF/VGA/CIF

Encoding Resolution

Main stream:

For 1080p stream access: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF@15 fps For 720p stream access: 720p/WD1/4CIF/VGA/CIF@15 fps

For SD stream access: WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) Sub-stream:

For 1080p and 720p stream access: CIF/QVGA@15 fps

For SD stream access: CIF/QVGA@25 fps (P)/30 fps (N)

Frame Rate

Video Bitrate 32 Kbps to 4 Mbps

Stream Type Video, Video & Audio

Audio Compression G.711u

Audio Bitrate 64 Kbps

Video and Audio

2-ch (upto 10-ch)

Up to 5 MP resolution

IP Video Input Support H.265+/H.265/H.264+/H.264 IP cameras

8-ch

Analog Video Input BNC interface (1.0 Vp-p, 75 Ω), supporting coaxial connection

HDTVI Input 1080p25, 1080p30, 720p25, 720p30

AHD Input 1080p25, 1080p30, 720p25, 720p30

HDCVI Input 1080p25, 1080p30, 720p25, 720p30

CVBS Input Support

HDMI Output 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz

VGA Output 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz

Video Output Mode HDMI/VGA simultaneous output

1-ch RCA (2.0Vp-p, 1 KΩ)

Audio Input

8-ch via coaxial cable