

# DS-7116HGHI-M1

DS-7116HGHI-M1 16-CH 720 MINI 1U H.265 DVR



Model	DS-7116HGHI-M1
Brend	Hikvision
Növ	XVR
Kanal sayı	16 kanal
Meqapixel	2 MP
Max HDD sayı	1 HDD
Max HDD həcmi	10 TB

## Specification

Motion Detection 2.0	
	Deep learning-based motiondetection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights;
Human/Vehicle Analysis	Quick search by object or event typeis supported;
Recording	
Video Compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Encoding Resolution	For 1080p streamaccess: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF For 720p stream access: 720p/WD1/4CIF/VGA/CIF For standard definition streamaccess: WD1/4CIF/VGA/CIF
Frame Rate	Main stream: For 1080p streamaccess: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF@15 fps For 720p stream access: 720p/WD1/4CIF/VGA/CIF@15 fps For SD stream access: WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) Sub-stream: For 1080pand 720p streamaccess: CIF/QVGA@15 fps For SD stream access:CIF/QVGA@25 fps (P)/30fps (N)
Video Bitrate	32 Kbps to 4Mbps
Stream Type	Video, Video& Audio
Audio Compression	G.711u
Audio Bitrate	64 Kbps
Video and Audio	

<b>IP Video Input</b>	2-ch (up to 18-ch) Up to 5 MP resolution Support H.265+/H.265/H.264+/H.264 IP cameras
<b>Analog Video Input</b>	16-ch BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection
<b>HDTV Input</b>	1080p25, 1080p30, 720p25, 720p30
<b>AHD Input</b>	1080p25, 1080p30, 720p25, 720p30
<b>HDCVI Input</b>	1080p25, 1080p30, 720p25, 720p30
<b>CVBS Input</b>	Support
<b>HDMI Output</b>	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
<b>VGA Output</b>	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
<b>Video Output Mode</b>	HDMI/VGA simultaneous output
<b>Audio Input</b>	1-ch RCA (2.0Vp-p, 1 KΩ) 16-ch via coaxial cable
<b>Audio Output</b>	1-ch, RCA (Linear, 1 KΩ)
<b>Two-Way Audio</b>	Reuse the first audio input
<b>Synchronous playback</b>	16-ch
<b>Network</b>	
<b>Total Bandwidth</b>	96 Mbps
<b>Network Protocol</b>	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP™, HTTPS
<b>Remote Connection</b>	128
<b>Network Interface</b>	1, RJ45 10/100Mbps self-adaptive Ethernet interface
<b>Auxiliary Interface</b>	
<b>SATA</b>	1 SATA interface
<b>Capacity</b>	Up to 10 TB capacity for each disk
<b>USB Interface</b>	Rear panel: 2 × USB 2.0
<b>General</b>	
<b>Power Supply</b>	12 VDC, 1.6 A
<b>Consumption</b>	≤ 7 W (without HDD)
<b>Working Temperature</b>	-10 °C to 55 °C (14 °F to +31 °F)
<b>Working Humidity</b>	10% to 90%
<b>Dimension (W × D × H)</b>	285 × 210 × 45 mm (11.2 × 8.3 × 1.8 inch)
<b>Weight</b>	≤ 1.8 kg (without HDD, 4.0 lb.)