HIKVISION

DS-7116HGHI-M1

Kod: 00-00004854 · Videoregistrator



DS-7116HGHI-M1 16-CH 720 MINI 1U H.265 DVR

Texniki göstəricilər

XVR	Növ
16 kanal	Kanal sayı
2 MP	Meqapixel
1 HDD	Max HDD sayı
10 TB	Max HDD həcmi

Ətraflı məlumat

Motion Detection 2.0	
Human/Vehicle Analysis	Deep learning-based motiondetection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights; Quick search by object or event typeis supported;
Recording	
Video Compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Encoding Resolution	For 1080p streamaccess: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF For 720p stream access: 720p/WD1/4CIF/VGA/CIF For standard definition streamaccess: WD1/4CIF/VGA/CIF
Frame Rate	Main stream: For 1080p streamaccess: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF@15 fps For 720p stream access: 720p/WD1/4CIF/VGA/CIF@15 fps For SD stream access: WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) Sub-stream: For 1080pand 720p streamaccess: CIF/QVGA@15 fps For SD stream access:CIF/QVGA@25 fps (P)/30fps (N)
Video Bitrate	32 Kbps to 4Mbps
Stream Type	Video, Video& Audio
Audio Compression	G.711u
Audio Bitrate	64 Kbps
Video and Audio	
IP Video Input	2-ch (up to 18-ch) Up to 5 MP resolution Support H.265+/H.265/H.264+/H.264 IP cameras
Analog VideoInput	16-ch BNC interface (1.0 Vp-p,75 Ω), supporting coaxitron connection

HDTVI Input	1080p25, 1080p30, 720p25, 720p30
AHD Input	1080p25, 1080p30, 720p25,720p30
HDCVI Input	1080p25, 1080p30, 720p25,720p30
CVBS Input	Support
HDMI Output	1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280× 720/60Hz
VGA Output	1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280× 720/60Hz
Video OutputMode	HDMI/VGA simultaneous output
Audio Input	1-ch RCA (2.0Vp-p, 1 KΩ) 16-ch via coaxial cable
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Two-Way Audio	Reuse the firstaudio input
Synchronous playback	16-ch
Network	
Total Bandwidth	96 Mbps
Network Protocol	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP™, HTTPS
Remote Connection	128
Network Interface	1, RJ45 10/100Mbps self-adaptive Ethernet interface
Auxiliary Interface	
SATA	1 SATA interface
Capacity	Up to 10 TB capacity for each disk
USB Interface	Rear panel: 2 × USB 2.0
General	
Power Supply	12 VDC, 1.6 A
Consumption	≤ 7 W (without HDD)
Working Temperature	-10 °C to 55 °C (14 °F to +31 °F)
Working Humidity	10% to 90%
Dimension (W × D × H)	285 × 210 × 45 mm (11.2× 8.3 × 1.8 inch)

Weight	≤ 1.8 kg (without HDD, 4.0 lb.)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az